

```
1 Last login: Tue Oct 18 10:09:06 on ttys000
2 Gandalf:~ pteeson$ cd /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl
3 Gandalf:GNUapl pteeson$ svn co
... http://svn.savannah.gnu.org/svn/apl/trunk > svn-log 2>&1
4 Gandalf:GNUapl pteeson$ cd trunk
5 Gandalf:trunk pteeson$ ./configure
6 checking for gcc... gcc
7 checking whether the C compiler works... yes
8 checking for C compiler default output file name... a.out
9 checking for suffix of executables...
10 checking whether we are cross compiling... no
11 checking for suffix of object files... o
12 checking whether we are using the GNU C compiler... yes
13 checking whether gcc accepts -g... yes
14 checking for gcc option to accept ISO C89... none needed
15 checking whether gcc understands -c and -o together... yes
16 checking how to run the C preprocessor... gcc -E
17 checking for grep that handles long lines and -e...
... /usr/bin/grep
18 checking for egrep... /usr/bin/grep -E
19 checking for ANSI C header files... yes
20 checking for sys/types.h... yes
21 checking for sys/stat.h... yes
22 checking for stdlib.h... yes
23 checking for string.h... yes
24 checking for memory.h... yes
25 checking for strings.h... yes
26 checking for inttypes.h... yes
27 checking for stdint.h... yes
28 checking for unistd.h... yes
29 checking minix/config.h usability... no
30 checking minix/config.h presence... no
31 checking for minix/config.h... no
32 checking whether it is safe to define __EXTENSIONS__... yes
33 checking for a BSD-compatible install... /usr/bin/install -c
34 checking whether build environment is sane... yes
35 checking for a thread-safe mkdir -p... ./install-sh -c -d
36 checking for gawk... no
37 checking for mawk... no
38 checking for nawk... no
39 checking for awk... awk
```

```
40 checking whether make sets $(MAKE)... yes
41 checking for style of include used by make... GNU
42 checking whether make supports nested variables... yes
43 checking dependency style of gcc... gcc3
44 checking whether to enable maintainer-specific portions of
... Makefiles... no
45 checking build system type... x86_64-apple-darwin18.7.0
46 checking host system type... x86_64-apple-darwin18.7.0
47 checking how to print strings... printf
48 checking for a sed that does not truncate output...
... /usr/bin/sed
49 checking for fgrep... /usr/bin/grep -F
50 checking for ld used by gcc...
... /Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld
51 checking if the linker
... (/Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld) is GNU ld... no
52 checking for BSD- or MS-compatible name lister (nm)...
... /usr/bin/nm -B
53 checking the name lister (/usr/bin/nm -B) interface... BSD nm
54 checking whether ln -s works... yes
55 checking the maximum length of command line arguments... 196608
56 checking how to convert x86_64-apple-darwin18.7.0 file names to
... x86_64-apple-darwin18.7.0 format... func_convert_file_noop
57 checking how to convert x86_64-apple-darwin18.7.0 file names to
... toolchain format... func_convert_file_noop
58 checking for
... /Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld option to reload object
... files... -r
59 checking for objdump... objdump
60 checking how to recognize dependent libraries... pass_all
61 checking for dlltool... no
62 checking how to associate runtime and link libraries... printf
... %s\n
63 checking for g++... g++
64 checking whether we are using the GNU C++ compiler... yes
65 checking whether g++ accepts -g... yes
66 checking dependency style of g++... gcc3
67 checking for ar... ar
```

```
68 checking for archiver @FILE support... no
69 checking for strip... strip
70 checking for ranlib... ranlib
71 checking command to parse /usr/bin/nm -B output from gcc
... object... ok
72 checking for sysroot... no
73 checking for a working dd... /bin/dd
74 checking how to truncate binary pipes... /bin/dd bs=4096
... count=1
75 checking for mt... no
76 checking if : is a manifest tool... no
77 checking for dsymutil... dsymutil
78 checking for nmedit... nmedit
79 checking for lipo... lipo
80 checking for otool... otool
81 checking for otool64... no
82 checking for -single_module linker flag... yes
83 checking for -exported_symbols_list linker flag... yes
84 checking for -force_load linker flag... yes
85 checking for dlfcn.h... yes
86 checking for objdir... .libs
87 checking if gcc supports -fno-rtti -fno-exceptions... yes
88 checking for gcc option to produce PIC... -fno-common -DPIC
89 checking if gcc PIC flag -fno-common -DPIC works... yes
90 checking if gcc static flag -static works... no
91 checking if gcc supports -c -o file.o... yes
92 checking if gcc supports -c -o file.o... (cached) yes
93 checking whether the gcc linker
... (/Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld) supports shared
... libraries... yes
94 checking dynamic linker characteristics... darwin18.7.0 dyld
95 checking how to hardcode library paths into programs...
... immediate
96 checking for dlopen in -ldl... yes
97 checking whether a program can dlopen itself... yes
98 checking whether a statically linked program can dlopen
... itself... yes
99 checking whether stripping libraries is possible... yes
100 checking if libtool supports shared libraries... yes
101 checking whether to build shared libraries... yes
```

```
102 checking whether to build static libraries... yes
103 checking how to run the C++ preprocessor... g++ -E
104 checking for ld used by g++...
... /Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld
105 checking if the linker
... (/Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld) is GNU ld... no
106 checking whether the g++ linker
... (/Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld) supports shared
... libraries... yes
107 checking for g++ option to produce PIC... -fno-common -DPIC
108 checking if g++ PIC flag -fno-common -DPIC works... yes
109 checking if g++ static flag -static works... no
110 checking if g++ supports -c -o file.o... yes
111 checking if g++ supports -c -o file.o... (cached) yes
112 checking whether the g++ linker
... (/Applications/Xcode.app/Contents/Developer/Toolchains/
... XcodeDefault.xctoolchain/usr/bin/ld) supports shared
... libraries... yes
113 checking dynamic linker characteristics... darwin18.7.0 dyld
114 checking how to hardcode library paths into programs...
... immediate
115 checking whether we are using the GNU C++ compiler... (cached)
... yes
116 checking whether g++ accepts -g... (cached) yes
117 checking dependency style of g++... (cached) gcc3
118 checking for gcc... (cached) gcc
119 checking whether we are using the GNU C compiler... (cached)
... yes
120 checking whether gcc accepts -g... (cached) yes
121 checking for gcc option to accept ISO C89... (cached) none
... needed
122 checking whether gcc understands -c and -o together... (cached)
... yes
123 checking ncurses.h usability... yes
124 checking ncurses.h presence... yes
125 checking for ncurses.h... yes
126 checking for term.h... yes
127 checking dirent.h usability... yes
```

```
128 checking dirent.h presence... yes
129 checking for dirent.h... yes
130 checking execinfo.h usability... yes
131 checking execinfo.h presence... yes
132 checking for execinfo.h... yes
133 checking fcntl.h usability... yes
134 checking fcntl.h presence... yes
135 checking for fcntl.h... yes
136 checking fftw3.h usability... no
137 checking fftw3.h presence... no
138 checking for fftw3.h... no
139 checking for inttypes.h... (cached) yes
140 checking png.h usability... yes
141 checking png.h presence... yes
142 checking for png.h... yes
143 checking for stdint.h... (cached) yes
144 checking for stdlib.h... (cached) yes
145 checking for string.h... (cached) yes
146 checking for strings.h... (cached) yes
147 checking for unistd.h... (cached) yes
148 checking utmpx.h usability... yes
149 checking utmpx.h presence... yes
150 checking for utmpx.h... yes
151 checking sys/un.h usability... yes
152 checking sys/un.h presence... yes
153 checking for sys/un.h... yes
154 checking ext/atomicity.h usability... no
155 checking ext/atomicity.h presence... no
156 checking for ext/atomicity.h... no
157 checking xcb/xcb.h usability... no
158 checking xcb/xcb.h presence... no
159 checking for xcb/xcb.h... no
160 checking zlib.h usability... yes
161 checking zlib.h presence... yes
162 checking for zlib.h... yes
163 checking X11/Xlib.h usability... no
164 checking X11/Xlib.h presence... no
165 checking for X11/Xlib.h... no
166 checking X11/Xlib-xcb.h usability... no
167 checking X11/Xlib-xcb.h presence... no
168 checking for X11/Xlib-xcb.h... no
```

```
169 checking X11/Xutil.h usability... no
170 checking X11/Xutil.h presence... no
171 checking for X11/Xutil.h... no
172 checking for xcb/xproto.h... no
173 checking for stdbool.h that conforms to C99... no
174 checking for _Bool... no
175 checking for inline... inline
176 checking for int32_t... yes
177 checking for int64_t... yes
178 checking for off_t... yes
179 checking for size_t... yes
180 checking for uint32_t... yes
181 checking for uint64_t... yes
182 checking for uint8_t... yes
183 checking for error_at_line... no
184 checking for stdlib.h... (cached) yes
185 checking for unistd.h... (cached) yes
186 checking for sys/param.h... yes
187 checking for getpagesize... yes
188 checking for working mmap... yes
189 checking for floor... yes
190 checking for memset... yes
191 checking for munmap... yes
192 checking for pow... yes
193 checking for sqrt... yes
194 checking for strchr... yes
195 checking for strerror... yes
196 checking for uncompress in -lz... yes
197 checking for XGetXCBConnection in -lX11-xcb... no
198 checking for XOpenDisplay in -lX11... no
199 checking for xcb_connect in -lxcb... no
200 checking for tparm in -ltninfo... no
201 checking for socket in -lsocket... no
202 checking for sem_init in -lpthread... yes
203 checking for yp_all in -lnsl... no
204 checking for setupterm in -lcurses... yes
205 checking for setupterm in -lncurses... yes
206 checking for acosh in -lm... yes
207 checking for gtk_init in -lgtk-3... no
208 checking for gdk_init in -lgdk-3... no
209 checking for fftw_plan_dft in -lfftw3... no
```

```
210 checking for backtrace in -lexecinfo... no
211 checking for dlopen in -ldl... (cached) yes
212 checking for cairo_fill in -lcairo... yes
213 checking for initState_r in -lc... no
214 checking for png_init_io in -lpng... yes
215 checking for __atomic_fetch_add_4 in -latomicity... no
216
217     *** checks for optional libraries ... ***
218
219 checking for SQLite3 library >= 3.0.0... yes
220 checking for pg_config... no
221 checking for pcre2_compile_32 in -lpcre2-32... no
222 checking whether support for GTK (needs GTK version 3) is
... desired... yes
223 checking for pkg-config... /usr/local/bin/pkg-config
224 checking if package gtk+-3.0 is installed... no
225 checking whether CPU has rdtsc (read CPU cycle counter)
... opcode... yes
226 checking whether gettimeofday exists... yes
227 checking whether sem_init() works... no
228 checking whether pthread_setaffinity_np is available... no
229 checking whether pthread_setname_np is available... no
230 checking whether OSAAtomicAdd32Barrier() is available... no
231 checking whether atomic_add_32_nv() is available... no
232
233     *** decisions made by the user ... ***
234
235 checking if user wants ctrl-d to be del-char (moving EOT to
... ctrl-z)... no
236 checking if we are compiling for Android... no
237 checking if we want to build an erlang interface (implies
... libapl.so)... no
238 checking if we want to build libapl.so... no
239 checking if we want to build libpython_apl.so... no
240 checking whether internal performance counters shall be
... enabled)... no
241 checking whether to remember the history of APL values (debug
... feature)... no
242 checking whether gprof profiling shall be enabled... no
243 checking whether gcov coverage testing shall be enabled... no
244 checking whether dynamic logging shall be enabled... no
```

```
245 checking whether value flags shall be traced... no
246 checking how picky internal tests shall be... 1
247 checking security level (0=none, 1=configured in preferences,
... 2=all)... 0
248 checking how many CPU cores shall be used by APL
... (experimental!)... 0
249 checking which type of socket APserver shall use... 0
250 checking which port number APserver shall use for TCP or UDP
... sockets... 16366
251 checking which unix port name APserver shall use...
... /tmp/GNU-APL/APserver
252 checking how long a short APL value shall be at most... 12
253 checking whether visible markers shall be used... no
254 checking whether support for rational numbers is desired ... no
255 checking whether we compile for an i686 CPU... no
256
257 checking that generated files are newer than configure... done
258 configure: creating ./config.status
259 config.status: creating Makefile
260 config.status: creating build/Makefile
261 config.status: creating debian/Makefile
262 config.status: creating debian/source/Makefile
263 config.status: creating doc/Makefile
264 config.status: creating doc/DALY/Makefile
265 config.status: creating erlang/Makefile
266 config.status: creating erlang/apl.erl
267 config.status: creating gnu-apl.d/Makefile
268 config.status: creating gnu-apl.d/preferences
269 config.status: creating HOWTOs/Makefile
270 config.status: creating rpm/Makefile
271 config.status: creating rpm/apl.spec
272 config.status: creating src/Makefile
273 config.status: creating src/APs/Makefile
274 config.status: creating src/Gtk/Makefile
275 config.status: creating src/emacs_mode/Makefile
276 config.status: creating src/native/Makefile
277 config.status: creating src/sql/Makefile
278 config.status: creating src/testcases/Makefile
279 config.status: creating src/workspaces/Makefile
280 config.status: creating support-files/Makefile
281 config.status: creating
```

```
281... support-files/105-key-International-Keyboard/Makefile
282 config.status: creating support-files/Bill_Daly_Ubuntu/Makefile
283 config.status: creating support-files/Dirk/Makefile
284 config.status: creating support-files/Dyalog-Keyboard/Makefile
285 config.status: creating support-files/Juergen-Mint-19/Makefile
286 config.status: creating support-files/old-Keyboard/Makefile
287 config.status: creating support-files/OS-X-Keyboard/Makefile
288 config.status: creating support-files/Unicomp-Keyboard/Makefile
289 config.status: creating support-files/WASD-Keyboard/Makefile
290 config.status: creating tools/Makefile
291 config.status: creating websock/Makefile
292 config.status: creating websock/client/Makefile
293 config.status: creating websock/server/Makefile
294 config.status: creating workspaces/Makefile
295 config.status: creating wslib3/Makefile
296 config.status: creating wslib3/DALY/Makefile
297 config.status: creating wslib4/Makefile
298 config.status: creating wslib5/Makefile
299 config.status: creating wslib5/APLComponentFiles/Makefile
300 config.status: creating wslib5/DALY/Makefile
301 config.status: creating wslib5/iso-apl-cf/Makefile
302 config.status: creating config.h
303 config.status: executing depfiles commands
304 config.status: executing libtool commands
305
306 configure: creating buildtag.hh...
307 readlink: illegal option -- f
308 usage: readlink [-n] [file ...]
309 configure: top-level apl directory is:
310 configure: removing old ./makefile.h
311
312 Gandalf:trunk pteeson$ make
313 creating a fresh makefile.h...
314 /Applications/Xcode.app/Contents/Developer/usr/bin/make
... all-recursive
315 Making all in workspaces
316 make[2]: Nothing to be done for `all'.
317 Making all in wslib3
318 Making all in DALY
319 make[3]: Nothing to be done for `all'.
320 make[3]: Nothing to be done for `all-am'.
```

```
321 Making all in wslib4
322 make[2]: Nothing to be done for `all'.
323 Making all in wslib5
324 Making all in APLComponentFiles
325 make[3]: Nothing to be done for `all'.
326 Making all in DALY
327 make[3]: Nothing to be done for `all'.
328 Making all in iso-apl-cf
329 make[3]: Nothing to be done for `all'.
330 make[3]: Nothing to be done for `all-am'.
331 Making all in build
332 make[2]: Nothing to be done for `all'.
333 Making all in doc
334 Making all in DALY
335 make[3]: Nothing to be done for `all'.
336 /bin/sh /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk/missing
... makeinfo apl.texi -o apl.info --no-split || touch apl.info
337 apl.texi:4: warning: unrecognized encoding name `UTF-8'.
338 apl.texi:2547: Unknown command `sup'.
339 apl.texi:2547: Misplaced {.
340 apl.texi:2547: Misplaced }.
341 apl.texi:2547: Unknown command `sup'.
342 apl.texi:2547: Misplaced {.
343 apl.texi:2547: Misplaced }.
344 apl.texi:2548: Unknown command `sub'.
345 apl.texi:2548: Misplaced {.
346 apl.texi:2548: Misplaced }.
347 apl.texi:2548: Unknown command `sub'.
348 apl.texi:2548: Misplaced {.
349 apl.texi:2548: Misplaced }.
350 apl.texi:2552: Unknown command `sub'.
351 apl.texi:2552: Misplaced {.
352 apl.texi:2552: Misplaced }.
353 apl.texi:3549: Unknown command `sub'.
354 apl.texi:3549: Misplaced {.
355 apl.texi:3549: Misplaced }.
356 apl.texi:3549: Unknown command `sub'.
357 apl.texi:3549: Misplaced {.
358 apl.texi:3549: Misplaced }.
359 apl.texi:4486: Unknown command `sub'.
360 apl.texi:4486: Misplaced {.
```

```
361 apl.texi:4486: Misplaced }.  
362 apl.texi:4486: Unknown command `sub'.  
363 apl.texi:4486: Misplaced {.  
364 apl.texi:4486: Misplaced }.  
365 apl.texi:4486: Unknown command `sub'.  
366 apl.texi:4486: Misplaced {.  
367 apl.texi:4486: Misplaced }.  
368 apl.texi:4487: Unknown command `sub'.  
369 apl.texi:4487: Misplaced {.  
370 apl.texi:4487: Misplaced }.  
371 apl.texi:4488: Unknown command `sub'.  
372 apl.texi:4488: Misplaced {.  
373 apl.texi:4488: Misplaced }.  
374 apl.texi:4489: Unknown command `sub'.  
375 apl.texi:4489: Misplaced {.  
376 apl.texi:4489: Misplaced }.  
377 apl.texi:4490: Unknown command `sub'.  
378 apl.texi:4490: Misplaced {.  
379 apl.texi:4490: Misplaced }.  
380 /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk/doc//apl.texi:3752:  
... `Output File Format' has no Up field (perhaps incorrect  
... sectioning?).  
381 makeinfo: Removing output file `apl.info' due to errors; use  
... --force to preserve.  
382 /bin/sh /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk/missing  
... makeinfo --html apl.texi -o apl.html --no-split || touch  
... apl.html  
383 apl.texi:4: warning: unrecognized encoding name `UTF-8'.  
384 apl.texi:2547: Unknown command `sup'.  
385 apl.texi:2547: Misplaced {.  
386 apl.texi:2547: Misplaced }.  
387 apl.texi:2547: Unknown command `sup'.  
388 apl.texi:2547: Misplaced {.  
389 apl.texi:2547: Misplaced }.  
390 apl.texi:2548: Unknown command `sub'.  
391 apl.texi:2548: Misplaced {.  
392 apl.texi:2548: Misplaced }.  
393 apl.texi:2548: Unknown command `sub'.  
394 apl.texi:2548: Misplaced {.  
395 apl.texi:2548: Misplaced }.  
396 apl.texi:2552: Unknown command `sub'.
```

```
397 apl.texi:2552: Misplaced {.
398 apl.texi:2552: Misplaced }.
399 apl.texi:3549: Unknown command `sub'.
400 apl.texi:3549: Misplaced {.
401 apl.texi:3549: Misplaced }.
402 apl.texi:3549: Unknown command `sub'.
403 apl.texi:3549: Misplaced {.
404 apl.texi:3549: Misplaced }.
405 apl.texi:4486: Unknown command `sub'.
406 apl.texi:4486: Misplaced {.
407 apl.texi:4486: Misplaced }.
408 apl.texi:4486: Unknown command `sub'.
409 apl.texi:4486: Misplaced {.
410 apl.texi:4486: Misplaced }.
411 apl.texi:4486: Unknown command `sub'.
412 apl.texi:4486: Misplaced {.
413 apl.texi:4486: Misplaced }.
414 apl.texi:4487: Unknown command `sub'.
415 apl.texi:4487: Misplaced {.
416 apl.texi:4487: Misplaced }.
417 apl.texi:4488: Unknown command `sub'.
418 apl.texi:4488: Misplaced {.
419 apl.texi:4488: Misplaced }.
420 apl.texi:4489: Unknown command `sub'.
421 apl.texi:4489: Misplaced {.
422 apl.texi:4489: Misplaced }.
423 apl.texi:4490: Unknown command `sub'.
424 apl.texi:4490: Misplaced {.
425 apl.texi:4490: Misplaced }.
426 /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk/doc//apl.texi:3752:
... `Output File Format' has no Up field (perhaps incorrect
... sectioning?).
427 makeinfo: Removing output file `apl.html' due to errors; use
... --force to preserve.
428 Making all in erlang
429 nothing to be done because GNU APL was NOT configured
... --with-erlang
430 Making all in gnu-apl.d
431 make[2]: Nothing to be done for `all'.
432 Making all in HOWTOs
433 if [ -z `which asciidoc` ] ; then touch
```

```
433.. GNU-APL-Memory-Management.html ; \
434     else asciidoc -a icons -o GNU-APL-Memory-Management.html
... GNU-APL-Memory-Management.asciidoc ; \
435         sed -i 's|<pre><code>|<pre>\n\n<code>|'
... GNU-APL-Memory-Management.html ; \
436         sed -i 's|</code></pre>|</code>\n\n</pre>|'
... GNU-APL-Memory-Management.html ; fi
437 Making all in src
438 Making all in native
439 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_file_io_la-file_io.lo -MD -MP -MF
... .deps/lib_file_io_la-file_io.Tpo -c -o
... lib_file_io_la-file_io.lo `test -f 'file_io.cc' || echo
... './'`file_io.cc
440 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_file_io_la-file_io.lo -MD -MP -MF
... .deps/lib_file_io_la-file_io.Tpo -c file_io.cc -fno-common
... -DPIC -o .libs/lib_file_io_la-file_io.o
441 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_file_io_la-file_io.lo -MD -MP -MF
... .deps/lib_file_io_la-file_io.Tpo -c file_io.cc -o
... lib_file_io_la-file_io.o >/dev/null 2>&1
442 mv -f .deps/lib_file_io_la-file_io.Tpo
... .deps/lib_file_io_la-file_io.Plo
443 /bin/sh ../../libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -avoid-version -export-dynamic -o lib_file_io_la -rpath
... /usr/local/lib/apl lib_file_io_la-file_io.lo -lpng -lcairo
... -ldl -lm -lcurses -lcurses -lpthread -lz
444 libtool: link:  g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/lib_file_io.dylib
... .libs/lib_file_io_la-file_io.o -lpng -lcairo -ldl -lm
... -lcurses -lcurses -lpthread -lz -g -O2 -g -O2 -install_name
... /usr/local/lib/apl/lib_file_io.dylib -Wl,-single_module
445 libtool: link:  ar cr .libs/lib_file_io.a
... lib_file_io_la-file_io.o
446 libtool: link:  ranlib .libs/lib_file_io.a
```

```
447 libtool: link: ( cd ".libs" && rm -f "lib_file_io.la" && ln -s
... "../lib_file_io.la" "lib_file_io.la" )
448 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_F0_la-template_F0.lo -MD -MP -MF
... .deps/lib_template_F0_la-template_F0.Tpo -c -o
... lib_template_F0_la-template_F0.lo `test -f 'template_F0.cc' ||
... echo './`template_F0.cc
449 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_F0_la-template_F0.lo -MD -MP -MF
... .deps/lib_template_F0_la-template_F0.Tpo -c template_F0.cc
... -fno-common -DPIC -o .libs/lib_template_F0_la-template_F0.o
450 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_F0_la-template_F0.lo -MD -MP -MF
... .deps/lib_template_F0_la-template_F0.Tpo -c template_F0.cc -o
... lib_template_F0_la-template_F0.o >/dev/null 2>&1
451 mv -f .deps/lib_template_F0_la-template_F0.Tpo
... .deps/lib_template_F0_la-template_F0.Plo
452 /bin/sh ../../libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -avoid-version -export-dynamic -o lib_template_F0.la -rpath
... /usr/local/lib/apl lib_template_F0_la-template_F0.lo -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
453 libtool: link: g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/lib_template_F0.dylib
... .libs/lib_template_F0_la-template_F0.o -lpng -lcairo -ldl -lm
... -lncurses -lcurses -lpthread -lz -g -O2 -g -O2 -install_name
... /usr/local/lib/apl/lib_template_F0.dylib -Wl,-single_module
454 libtool: link: ar cr .libs/lib_template_F0.a
... lib_template_F0_la-template_F0.o
455 libtool: link: ranlib .libs/lib_template_F0.a
456 libtool: link: ( cd ".libs" && rm -f "lib_template_F0.la" && ln
... -s "../lib_template_F0.la" "lib_template_F0.la" )
457 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_F12_la-template_F12.lo -MD -MP -MF
... .deps/lib_template_F12_la-template_F12.Tpo -c -o
```

```
457... lib_template_F12_la-template_F12.lo `test -f 'template_F12.cc'
... || echo './`template_F12.cc
458 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_F12_la-template_F12.lo -MD -MP -MF
... .deps/lib_template_F12_la-template_F12.Tpo -c template_F12.cc
... -fno-common -DPIC -o .libs/lib_template_F12_la-template_F12.o
459 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_F12_la-template_F12.lo -MD -MP -MF
... .deps/lib_template_F12_la-template_F12.Tpo -c template_F12.cc
... -o lib_template_F12_la-template_F12.o >/dev/null 2>&1
460 mv -f .deps/lib_template_F12_la-template_F12.Tpo
... .deps/lib_template_F12_la-template_F12.Plo
461 /bin/sh .././libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -avoid-version -export-dynamic -o lib_template_F12_la-template_F12.o
... /usr/local/lib/apl lib_template_F12_la-template_F12.lo -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
462 libtool: link: g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/lib_template_F12.dylib
... .libs/lib_template_F12_la-template_F12.o -lpng -lcairo -ldl
... -lm -lncurses -lcurses -lpthread -lz -g -O2 -g -O2
... -install_name /usr/local/lib/apl/lib_template_F12.dylib
... -Wl,-single_module
463 libtool: link: ar cr .libs/lib_template_F12.a
... lib_template_F12_la-template_F12.o
464 libtool: link: ranlib .libs/lib_template_F12.a
465 libtool: link: ( cd ".libs" && rm -f "lib_template_F12_la" &&
... ln -s "../lib_template_F12_la" "lib_template_F12_la" )
466 /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_OP1_la-template_OP1.lo -MD -MP -MF
... .deps/lib_template_OP1_la-template_OP1.Tpo -c -o
... lib_template_OP1_la-template_OP1.lo `test -f 'template_OP1.cc'
... || echo './`template_OP1.cc
467 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_OP1_la-template_OP1.lo -MD -MP -MF
... .deps/lib_template_OP1_la-template_OP1.Tpo -c template_OP1.cc
```

```
467... -fno-common -DPIC -o .libs/lib_template_OP1_la-template_OP1.o
468 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_OP1_la-template_OP1.lo -MD -MP -MF
... .deps/lib_template_OP1_la-template_OP1.Tpo -c template_OP1.cc
... -o lib_template_OP1_la-template_OP1.o >/dev/null 2>&1
469 mv -f .deps/lib_template_OP1_la-template_OP1.Tpo
... .deps/lib_template_OP1_la-template_OP1.Plo
470 /bin/sh .././libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -avoid-version -export-dynamic -o lib_template_OP1.la -rpath
... /usr/local/lib/apl lib_template_OP1_la-template_OP1.lo -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
471 libtool: link: g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/lib_template_OP1.dylib
... .libs/lib_template_OP1_la-template_OP1.o -lpng -lcairo -ldl
... -lm -lncurses -lcurses -lpthread -lz -g -O2 -g -O2
... -install_name /usr/local/lib/apl/lib_template_OP1.dylib
... -Wl,-single_module
472 libtool: link: ar cr .libs/lib_template_OP1.a
... lib_template_OP1_la-template_OP1.o
473 libtool: link: ranlib .libs/lib_template_OP1.a
474 libtool: link: ( cd ".libs" && rm -f "lib_template_OP1.la" &&
... ln -s "../lib_template_OP1.la" "lib_template_OP1.la" )
475 /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_OP2_la-template_OP2.lo -MD -MP -MF
... .deps/lib_template_OP2_la-template_OP2.Tpo -c -o
... lib_template_OP2_la-template_OP2.lo `test -f 'template_OP2.cc'
... || echo './`template_OP2.cc
476 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_OP2_la-template_OP2.lo -MD -MP -MF
... .deps/lib_template_OP2_la-template_OP2.Tpo -c template_OP2.cc
... -fno-common -DPIC -o .libs/lib_template_OP2_la-template_OP2.o
477 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... lib_template_OP2_la-template_OP2.lo -MD -MP -MF
... .deps/lib_template_OP2_la-template_OP2.Tpo -c template_OP2.cc
... -o lib_template_OP2_la-template_OP2.o >/dev/null 2>&1
```

```
478 mv -f .deps/lib_template_OP2_la-template_OP2.Tpo
... .deps/lib_template_OP2_la-template_OP2.Plo
479 /bin/sh ../../libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -avoid-version -export-dynamic -o lib_template_OP2.la -rpath
... /usr/local/lib/apl lib_template_OP2_la-template_OP2.lo -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
480 libtool: link: g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/lib_template_OP2.dylib
... .libs/lib_template_OP2_la-template_OP2.o -lpng -lcairo -ldl
... -lm -lncurses -lcurses -lpthread -lz -g -O2 -g -O2
... -install_name /usr/local/lib/apl/lib_template_OP2.dylib
... -Wl,-single_module
481 libtool: link: ar cr .libs/lib_template_OP2.a
... lib_template_OP2_la-template_OP2.o
482 libtool: link: ranlib .libs/lib_template_OP2.a
483 libtool: link: ( cd ".libs" && rm -f "lib_template_OP2.la" &&
... ln -s "../../lib_template_OP2.la" "lib_template_OP2.la" )
484 Making all in APs
485 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT AP100-AP100.o
... -MD -MP -MF .deps/AP100-AP100.Tpo -c -o AP100-AP100.o `test -f
... 'AP100.cc' || echo './'`AP100.cc
486 mv -f .deps/AP100-AP100.Tpo .deps/AP100-AP100.Po
487 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT AP100-APmain.o
... -MD -MP -MF .deps/AP100-APmain.Tpo -c -o AP100-APmain.o `test
... -f 'APmain.cc' || echo './'`APmain.cc
488 mv -f .deps/AP100-APmain.Tpo .deps/AP100-APmain.Po
489 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... ../AP100-Backtrace.o -MD -MP -MF ../.deps/AP100-Backtrace.Tpo
... -c -o ../AP100-Backtrace.o `test -f '../Backtrace.cc' || echo
... './'`../Backtrace.cc
490 mv -f ../.deps/AP100-Backtrace.Tpo ../.deps/AP100-Backtrace.Po
491 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
```

```
491... ../AP100-Svar_DB.o -MD -MP -MF ../.deps/AP100-Svar_DB.Tpo -c -o
... ../AP100-Svar_DB.o `test -f '../Svar_DB.cc' || echo
... './'`../Svar_DB.cc
492 mv -f ../.deps/AP100-Svar_DB.Tpo ../.deps/AP100-Svar_DB.Po
493 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... ../AP100-Svar_record.o -MD -MP -MF
... ../.deps/AP100-Svar_record.Tpo -c -o ../AP100-Svar_record.o
... `test -f '../Svar_record.cc' || echo './'`../Svar_record.cc
494 mv -f ../.deps/AP100-Svar_record.Tpo
... ../.deps/AP100-Svar_record.Po
495 /bin/sh .././libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o AP100
... AP100-AP100.o AP100-APmain.o ../AP100-Backtrace.o
... ../AP100-Svar_DB.o ../AP100-Svar_record.o -lpng -lcairo -ldl
... -lm -lncurses -lcurses -lpthread -lz
496 libtool: link: g++ -I ../.. -g -O2 -DAP_NUM=100 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o AP100
... AP100-AP100.o AP100-APmain.o ../AP100-Backtrace.o
... ../AP100-Svar_DB.o ../AP100-Svar_record.o -Wl,-bind_at_load
... -lpng -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
497 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT AP210-AP210.o
... -MD -MP -MF .deps/AP210-AP210.Tpo -c -o AP210-AP210.o `test -f
... 'AP210.cc' || echo './'`AP210.cc
498 mv -f .deps/AP210-AP210.Tpo .deps/AP210-AP210.Po
499 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT AP210-APmain.o
... -MD -MP -MF .deps/AP210-APmain.Tpo -c -o AP210-APmain.o `test
... -f 'APmain.cc' || echo './'`APmain.cc
500 mv -f .deps/AP210-APmain.Tpo .deps/AP210-APmain.Po
501 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... ../AP210-Backtrace.o -MD -MP -MF ../.deps/AP210-Backtrace.Tpo
... -c -o ../AP210-Backtrace.o `test -f '../Backtrace.cc' || echo
... './'`../Backtrace.cc
```

```
502 mv -f ../.deps/AP210-Backtrace.Tpo ../.deps/AP210-Backtrace.Po
503 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... ../AP210-Svar_DB.o -MD -MP -MF ../.deps/AP210-Svar_DB.Tpo -c -o
... ../AP210-Svar_DB.o `test -f '../Svar_DB.cc' || echo
... './'`../Svar_DB.cc
504 mv -f ../.deps/AP210-Svar_DB.Tpo ../.deps/AP210-Svar_DB.Po
505 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2
... -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... ../AP210-Svar_record.o -MD -MP -MF
... ../.deps/AP210-Svar_record.Tpo -c -o ../AP210-Svar_record.o
... `test -f '../Svar_record.cc' || echo './'`../Svar_record.cc
506 mv -f ../.deps/AP210-Svar_record.Tpo
... ../.deps/AP210-Svar_record.Po
507 /bin/sh .././libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o AP210
... AP210-AP210.o AP210-APmain.o ../AP210-Backtrace.o
... ../AP210-Svar_DB.o ../AP210-Svar_record.o -lpng -lcairo -ldl
... -lm -lncurses -lcurses -lpthread -lz
508 libtool: link: g++ -I ../.. -g -O2 -DAP_NUM=210 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o AP210
... AP210-AP210.o AP210-APmain.o ../AP210-Backtrace.o
... ../AP210-Svar_DB.o ../AP210-Svar_record.o -Wl,-bind_at_load
... -lpng -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
509 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... APserver-APserver.o -MD -MP -MF .deps/APserver-APserver.Tpo -c
... -o APserver-APserver.o `test -f 'APserver.cc' || echo
... './'`APserver.cc
510 mv -f .deps/APserver-APserver.Tpo .deps/APserver-APserver.Po
511 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... APserver-Svar_DB_server.o -MD -MP -MF
... .deps/APserver-Svar_DB_server.Tpo -c -o
... APserver-Svar_DB_server.o `test -f 'Svar_DB_server.cc' || echo
... './'`Svar_DB_server.cc
512 mv -f .deps/APserver-Svar_DB_server.Tpo
... .deps/APserver-Svar_DB_server.Po
```

```

513 g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... ../APserver-Svar_record.o -MD -MP -MF
... ../.deps/APserver-Svar_record.Tpo -c -o
... ../APserver-Svar_record.o `test -f '../Svar_record.cc' || echo
... './'`../Svar_record.cc
514 mv -f ../.deps/APserver-Svar_record.Tpo
... ../.deps/APserver-Svar_record.Po
515 /bin/sh .././libtool --tag=CXX --mode=link g++ -I ../.. -g
... -O2 -g -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o
... APserver APserver-APserver.o APserver-Svar_DB_server.o
... ../APserver-Svar_record.o -lpng -lcairo -ldl -lm -lncurses
... -lcurses -lpthread -lz
516 libtool: link: g++ -I ../.. -g -O2 -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o APserver
... APserver-APserver.o APserver-Svar_DB_server.o
... ../APserver-Svar_record.o -Wl,-bind_at_load -lpng -lcairo -ldl
... -lm -lncurses -lcurses -lpthread -lz
517 Making all in emacs_mode
518 depbase=`echo DefCommand.lo | sed
... 's|[^/]*$|.deps/&;s|\.lo$||'`; \
519 /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... DefCommand.lo -MD -MP -MF $depbase.Tpo -c -o DefCommand.lo
... DefCommand.cc && \
520 mv -f $depbase.Tpo $depbase.Plo
521 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT DefCommand.lo
... -MD -MP -MF .deps/DefCommand.Tpo -c DefCommand.cc -fno-common
... -DPIC -o .libs/DefCommand.o
522 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT DefCommand.lo
... -MD -MP -MF .deps/DefCommand.Tpo -c DefCommand.cc -o
... DefCommand.o >/dev/null 2>&1
523 depbase=`echo emacs.lo | sed 's|[^/]*$|.deps/&;s|\.lo$||'`; \
524 /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT emacs.lo

```

```
524... -MD -MP -MF $depbases.Tpo -c -o emacs.lo emacs.cc &&\
525     mv -f $depbases.Tpo $depbases.Plo
526 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT emacs.lo -MD
... -MP -MF .deps/emacs.Tpo -c emacs.cc -fno-common -DPIC -o
... .libs/emacs.o
527 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT emacs.lo -MD
... -MP -MF .deps/emacs.Tpo -c emacs.cc -o emacs.o >/dev/null 2>&1
528 depbase=`echo FnCommand.lo | sed
... 's|[^/]*$|.deps/&;s|\.lo$||'`; \
529     /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... FnCommand.lo -MD -MP -MF $depbases.Tpo -c -o FnCommand.lo
... FnCommand.cc &&\
530     mv -f $depbases.Tpo $depbases.Plo
531 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT FnCommand.lo
... -MD -MP -MF .deps/FnCommand.Tpo -c FnCommand.cc -fno-common
... -DPIC -o .libs/FnCommand.o
532 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT FnCommand.lo
... -MD -MP -MF .deps/FnCommand.Tpo -c FnCommand.cc -o FnCommand.o
... >/dev/null 2>&1
533 depbase=`echo FnTagCommand.lo | sed
... 's|[^/]*$|.deps/&;s|\.lo$||'`; \
534     /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... FnTagCommand.lo -MD -MP -MF $depbases.Tpo -c -o FnTagCommand.lo
... FnTagCommand.cc &&\
535     mv -f $depbases.Tpo $depbases.Plo
536 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT FnTagCommand.lo
... -MD -MP -MF .deps/FnTagCommand.Tpo -c FnTagCommand.cc
```

```
536... -fno-common -DPIC -o .libs/FnTagCommand.o
537 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT FnTagCommand.lo
... -MD -MP -MF .deps/FnTagCommand.Tpo -c FnTagCommand.cc -o
... FnTagCommand.o >/dev/null 2>&1
538 depbase=`echo FollowCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\..lo$||'`; \
539 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... FollowCommand.lo -MD -MP -MF $depbase.Tpo -c -o
... FollowCommand.lo FollowCommand.cc && \
540 mv -f $depbase.Tpo $depbase.Plo
541 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... FollowCommand.lo -MD -MP -MF .deps/FollowCommand.Tpo -c
... FollowCommand.cc -fno-common -DPIC -o .libs/FollowCommand.o
542 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... FollowCommand.lo -MD -MP -MF .deps/FollowCommand.Tpo -c
... FollowCommand.cc -o FollowCommand.o >/dev/null 2>&1
543 depbase=`echo GetVarCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\..lo$||'`; \
544 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... GetVarCommand.lo -MD -MP -MF $depbase.Tpo -c -o
... GetVarCommand.lo GetVarCommand.cc && \
545 mv -f $depbase.Tpo $depbase.Plo
546 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... GetVarCommand.lo -MD -MP -MF .deps/GetVarCommand.Tpo -c
... GetVarCommand.cc -fno-common -DPIC -o .libs/GetVarCommand.o
547 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... GetVarCommand.lo -MD -MP -MF .deps/GetVarCommand.Tpo -c
```

```
547... GetVarCommand.cc -o GetVarCommand.o >/dev/null 2>&1
548 depbase=`echo HelpCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
549 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... HelpCommand.lo -MD -MP -MF $depbase.Tpo -c -o HelpCommand.lo
... HelpCommand.cc && \
550 mv -f $depbase.Tpo $depbase.Plo
551 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT HelpCommand.lo
... -MD -MP -MF .deps/HelpCommand.Tpo -c HelpCommand.cc
... -fno-common -DPIC -o .libs/HelpCommand.o
552 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT HelpCommand.lo
... -MD -MP -MF .deps/HelpCommand.Tpo -c HelpCommand.cc -o
... HelpCommand.o >/dev/null 2>&1
553 depbase=`echo Listener.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
554 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... Listener.lo -MD -MP -MF $depbase.Tpo -c -o Listener.lo
... Listener.cc && \
555 mv -f $depbase.Tpo $depbase.Plo
556 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT Listener.lo -MD
... -MP -MF .deps/Listener.Tpo -c Listener.cc -fno-common -DPIC -o
... .libs/Listener.o
557 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT Listener.lo -MD
... -MP -MF .deps/Listener.Tpo -c Listener.cc -o Listener.o
... >/dev/null 2>&1
558 depbase=`echo LockWrapper.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
559 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
```

```
559... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... LockWrapper.lo -MD -MP -MF $depbased.Plo -c -o LockWrapper.lo
... LockWrapper.cc &&\
560     mv -f $depbased.Plo $depbased.Plo
561 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT LockWrapper.lo
... -MD -MP -MF .deps/LockWrapper.Tpo -c LockWrapper.cc
... -fno-common -DPIC -o .libs/LockWrapper.o
562 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT LockWrapper.lo
... -MD -MP -MF .deps/LockWrapper.Tpo -c LockWrapper.cc -o
... LockWrapper.o >/dev/null 2>&1
563 depbase=`echo network.lo | sed 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
564     /bin/sh ../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... network.lo -MD -MP -MF $depbased.Plo -c -o network.lo network.cc
... &&\
565     mv -f $depbased.Plo $depbased.Plo
566 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT network.lo -MD
... -MP -MF .deps/network.Tpo -c network.cc -fno-common -DPIC -o
... .libs/network.o
567 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT network.lo -MD
... -MP -MF .deps/network.Tpo -c network.cc -o network.o >/dev/null
... 2>&1
568 depbase=`echo NetworkConnection.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
569     /bin/sh ../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... NetworkConnection.lo -MD -MP -MF $depbased.Plo -c -o
... NetworkConnection.lo NetworkConnection.cc &&\
570     mv -f $depbased.Plo $depbased.Plo
571 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
```

```
571... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... NetworkConnection.lo -MD -MP -MF .deps/NetworkConnection.Tpo -c
... NetworkConnection.cc -fno-common -DPIC -o
... .libs/NetworkConnection.o
572 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... NetworkConnection.lo -MD -MP -MF .deps/NetworkConnection.Tpo -c
... NetworkConnection.cc -o NetworkConnection.o >/dev/null 2>&1
573 depbase=`echo RunCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
574 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... RunCommand.lo -MD -MP -MF $depbase.Tpo -c -o RunCommand.lo
... RunCommand.cc && \
575 mv -f $depbase.Tpo $depbase.Plo
576 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT RunCommand.lo
... -MD -MP -MF .deps/RunCommand.Tpo -c RunCommand.cc -fno-common
... -DPIC -o .libs/RunCommand.o
577 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT RunCommand.lo
... -MD -MP -MF .deps/RunCommand.Tpo -c RunCommand.cc -o
... RunCommand.o >/dev/null 2>&1
578 depbase=`echo SicCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
579 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SicCommand.lo -MD -MP -MF $depbase.Tpo -c -o SicCommand.lo
... SicCommand.cc && \
580 mv -f $depbase.Tpo $depbase.Plo
581 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT SicCommand.lo
... -MD -MP -MF .deps/SicCommand.Tpo -c SicCommand.cc -fno-common
... -DPIC -o .libs/SicCommand.o
582 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
```

```
582... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT SicCommand.lo
... -MD -MP -MF .deps/SicCommand.Tpo -c SicCommand.cc -o
... SicCommand.o >/dev/null 2>&1
583 depbase=`echo SiCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\\.lo$||'`; \
584 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SiCommand.lo -MD -MP -MF $depbase.Tpo -c -o SiCommand.lo
... SiCommand.cc && \
585 mv -f $depbase.Tpo $depbase.Plo
586 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT SiCommand.lo
... -MD -MP -MF .deps/SiCommand.Tpo -c SiCommand.cc -fno-common
... -DPIC -o .libs/SiCommand.o
587 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT SiCommand.lo
... -MD -MP -MF .deps/SiCommand.Tpo -c SiCommand.cc -o SiCommand.o
... >/dev/null 2>&1
588 depbase=`echo SendCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\\.lo$||'`; \
589 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SendCommand.lo -MD -MP -MF $depbase.Tpo -c -o SendCommand.lo
... SendCommand.cc && \
590 mv -f $depbase.Tpo $depbase.Plo
591 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT SendCommand.lo
... -MD -MP -MF .deps/SendCommand.Tpo -c SendCommand.cc
... -fno-common -DPIC -o .libs/SendCommand.o
592 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT SendCommand.lo
... -MD -MP -MF .deps/SendCommand.Tpo -c SendCommand.cc -o
... SendCommand.o >/dev/null 2>&1
593 depbase=`echo SystemFnCommand.lo | sed
```

```

593.. 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
594   /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SystemFnCommand.lo -MD -MP -MF $depbased.Tpo -c -o
... SystemFnCommand.lo SystemFnCommand.cc && \
595   mv -f $depbased.Tpo $depbased.Plo
596 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SystemFnCommand.lo -MD -MP -MF .deps/SystemFnCommand.Tpo -c
... SystemFnCommand.cc -fno-common -DPIC -o
... .libs/SystemFnCommand.o
597 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SystemFnCommand.lo -MD -MP -MF .deps/SystemFnCommand.Tpo -c
... SystemFnCommand.cc -o SystemFnCommand.o >/dev/null 2>&1
598 depbase=`echo SystemVariableCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
599   /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SystemVariableCommand.lo -MD -MP -MF $depbased.Tpo -c -o
... SystemVariableCommand.lo SystemVariableCommand.cc && \
600   mv -f $depbased.Tpo $depbased.Plo
601 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SystemVariableCommand.lo -MD -MP -MF
... .deps/SystemVariableCommand.Tpo -c SystemVariableCommand.cc
... -fno-common -DPIC -o .libs/SystemVariableCommand.o
602 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SystemVariableCommand.lo -MD -MP -MF
... .deps/SystemVariableCommand.Tpo -c SystemVariableCommand.cc -o
... SystemVariableCommand.o >/dev/null 2>&1
603 depbase=`echo TcpListener.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
604   /bin/sh ../../libtool --tag=CXX --mode=compile g++

```

```
604... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... TcpListener.lo -MD -MP -MF $depbased.Tpo -c -o TcpListener.lo
... TcpListener.cc &&\
605     mv -f $depbased.Tpo $depbased.Plo
606 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT TcpListener.lo
... -MD -MP -MF .deps/TcpListener.Tpo -c TcpListener.cc
... -fno-common -DPIC -o .libs/TcpListener.o
607 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT TcpListener.lo
... -MD -MP -MF .deps/TcpListener.Tpo -c TcpListener.cc -o
... TcpListener.o >/dev/null 2>&1
608 depbase=`echo TempFileWrapper.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
609     /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... TempFileWrapper.lo -MD -MP -MF $depbased.Tpo -c -o
... TempFileWrapper.lo TempFileWrapper.cc &&\
610     mv -f $depbased.Tpo $depbased.Plo
611 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... TempFileWrapper.lo -MD -MP -MF .deps/TempFileWrapper.Tpo -c
... TempFileWrapper.cc -fno-common -DPIC -o
... .libs/TempFileWrapper.o
612 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... TempFileWrapper.lo -MD -MP -MF .deps/TempFileWrapper.Tpo -c
... TempFileWrapper.cc -o TempFileWrapper.o >/dev/null 2>&1
613 depbase=`echo TraceData.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||'`; \
614     /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... TraceData.lo -MD -MP -MF $depbased.Tpo -c -o TraceData.lo
... TraceData.cc &&\
```

```
615     mv -f $depbased.Tpo $depbased.Plo
616 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT TraceData.lo
... -MD -MP -MF .deps/TraceData.Tpo -c TraceData.cc -fno-common
... -DPIC -o .libs/TraceData.o
617 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT TraceData.lo
... -MD -MP -MF .deps/TraceData.Tpo -c TraceData.cc -o TraceData.o
... >/dev/null 2>&1
618 depbase=`echo UnixSocketListener.lo | sed
... 's|[^/]*$|.deps/&;s|\.lo$||'`; \
619     /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... UnixSocketListener.lo -MD -MP -MF $depbased.Tpo -c -o
... UnixSocketListener.lo UnixSocketListener.cc && \
620     mv -f $depbased.Tpo $depbased.Plo
621 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... UnixSocketListener.lo -MD -MP -MF .deps/UnixSocketListener.Tpo
... -c UnixSocketListener.cc -fno-common -DPIC -o
... .libs/UnixSocketListener.o
622 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... UnixSocketListener.lo -MD -MP -MF .deps/UnixSocketListener.Tpo
... -c UnixSocketListener.cc -o UnixSocketListener.o >/dev/null
... 2>&1
623 depbase=`echo util.lo | sed 's|[^/]*$|.deps/&;s|\.lo$||'`; \
624     /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT util.lo
... -MD -MP -MF $depbased.Tpo -c -o util.lo util.cc && \
625     mv -f $depbased.Tpo $depbased.Plo
626 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT util.lo -MD -MP
... -MF .deps/util.Tpo -c util.cc -fno-common -DPIC -o
```

```
626.. .libs/util.o
627 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT util.lo -MD -MP
... -MF .deps/util.Tpo -c util.cc -o util.o >/dev/null 2>&1
628 depbase=`echo VariablesCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\.\lo$||'`; \
629   /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... VariablesCommand.lo -MD -MP -MF $depbase.Tpo -c -o
... VariablesCommand.lo VariablesCommand.cc && \
630   mv -f $depbase.Tpo $depbase.Plo
631 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... VariablesCommand.lo -MD -MP -MF .deps/VariablesCommand.Tpo -c
... VariablesCommand.cc -fno-common -DPIC -o
... .libs/VariablesCommand.o
632 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... VariablesCommand.lo -MD -MP -MF .deps/VariablesCommand.Tpo -c
... VariablesCommand.cc -o VariablesCommand.o >/dev/null 2>&1
633 depbase=`echo VersionCommand.lo | sed
... 's|[^/]*$|.deps/&|;s|\.\lo$||'`; \
634   /bin/sh .././libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -Wno-deprecated-declarations -g
... -O2 -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... VersionCommand.lo -MD -MP -MF $depbase.Tpo -c -o
... VersionCommand.lo VersionCommand.cc && \
635   mv -f $depbase.Tpo $depbase.Plo
636 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... VersionCommand.lo -MD -MP -MF .deps/VersionCommand.Tpo -c
... VersionCommand.cc -fno-common -DPIC -o .libs/VersionCommand.o
637 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../..
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... VersionCommand.lo -MD -MP -MF .deps/VersionCommand.Tpo -c
```

```
637... VersionCommand.cc -o VersionCommand.o >/dev/null 2>&1
638 /bin/sh ../../libtool --tag=CXX --mode=link g++
... -Wno-deprecated-declarations -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -export-dynamic -o
... libemacs.la -rpath /usr/local/lib/apl DefCommand.lo emacs.lo
... FnCommand.lo FnTagCommand.lo FollowCommand.lo GetVarCommand.lo
... HelpCommand.lo Listener.lo LockWrapper.lo network.lo
... NetworkConnection.lo RunCommand.lo SicCommand.lo SiCommand.lo
... SendCommand.lo SystemFnCommand.lo SystemVariableCommand.lo
... TcpListener.lo TempFileWrapper.lo TraceData.lo
... UnixSocketListener.lo util.lo VariablesCommand.lo
... VersionCommand.lo -lpng -lcairo -ldl -lm -lncurses -lcurses
... -lpthread -lz
639 libtool: link: g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/libemacs.0.dylib
... .libs/DefCommand.o .libs/emacs.o .libs/FnCommand.o
... .libs/FnTagCommand.o .libs/FollowCommand.o
... .libs/GetVarCommand.o .libs/HelpCommand.o .libs/Listener.o
... .libs/LockWrapper.o .libs/network.o .libs/NetworkConnection.o
... .libs/RunCommand.o .libs/SicCommand.o .libs/SiCommand.o
... .libs/SendCommand.o .libs/SystemFnCommand.o
... .libs/SystemVariableCommand.o .libs/TcpListener.o
... .libs/TempFileWrapper.o .libs/TraceData.o
... .libs/UnixSocketListener.o .libs/util.o
... .libs/VariablesCommand.o .libs/VersionCommand.o -lpng -lcairo
... -ldl -lm -lncurses -lcurses -lpthread -lz -g -O2
... -install_name /usr/local/lib/apl/libemacs.0.dylib
... -compatibility_version 1 -current_version 1.0
... -Wl,-single_module
640 libtool: link: (cd ".libs" && rm -f "libemacs.dylib" && ln -s
... "libemacs.0.dylib" "libemacs.dylib")
641 libtool: link: ar cr .libs/libemacs.a DefCommand.o emacs.o
... FnCommand.o FnTagCommand.o FollowCommand.o GetVarCommand.o
... HelpCommand.o Listener.o LockWrapper.o network.o
... NetworkConnection.o RunCommand.o SicCommand.o SiCommand.o
... SendCommand.o SystemFnCommand.o SystemVariableCommand.o
... TcpListener.o TempFileWrapper.o TraceData.o
... UnixSocketListener.o util.o VariablesCommand.o VersionCommand.o
642 libtool: link: ranlib .libs/libemacs.a
643 libtool: link: ( cd ".libs" && rm -f "libemacs.la" && ln -s
... "../libemacs.la" "libemacs.la" )
```

```
644 Making all in sql
645 depbase=`echo apl-sqlite.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||`;\
646   /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I ../..
... -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-sqlite.lo
... -MD -MP -MF $depbase.Tpo -c -o apl-sqlite.lo apl-sqlite.cc &&\
647   mv -f $depbase.Tpo $depbase.Plo
648 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-sqlite.lo
... -MD -MP -MF .deps/apl-sqlite.Tpo -c apl-sqlite.cc -fno-common
... -DPIC -o .libs/apl-sqlite.o
649 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
650 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-sqlite.lo
... -MD -MP -MF .deps/apl-sqlite.Tpo -c apl-sqlite.cc -o
... apl-sqlite.o >/dev/null 2>&1
651 depbase=`echo Connection.lo | sed
... 's|[^/]*$|.deps/&|;s|\.lo$||`;\
652   /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I ../..
... -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT Connection.lo
... -MD -MP -MF $depbase.Tpo -c -o Connection.lo Connection.cc &&\
653   mv -f $depbase.Tpo $depbase.Plo
654 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT Connection.lo
... -MD -MP -MF .deps/Connection.Tpo -c Connection.cc -fno-common
... -DPIC -o .libs/Connection.o
655 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
656 libtool: compile:  g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT Connection.lo
... -MD -MP -MF .deps/Connection.Tpo -c Connection.cc -o
... Connection.o >/dev/null 2>&1
```

```
657 depbase=`echo SqliteArgListBuilder.lo | sed
... 's|[^/]*$|.deps/&;s|\.lo$||'`; \
658 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I ../..
... -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SqliteArgListBuilder.lo -MD -MP -MF $depbase.Tpo -c -o
... SqliteArgListBuilder.lo SqliteArgListBuilder.cc && \
659 mv -f $depbase.Tpo $depbase.Plo
660 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SqliteArgListBuilder.lo -MD -MP -MF
... .deps/SqliteArgListBuilder.Tpo -c SqliteArgListBuilder.cc
... -fno-common -DPIC -o .libs/SqliteArgListBuilder.o
661 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
662 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SqliteArgListBuilder.lo -MD -MP -MF
... .deps/SqliteArgListBuilder.Tpo -c SqliteArgListBuilder.cc -o
... SqliteArgListBuilder.o >/dev/null 2>&1
663 depbase=`echo SqliteConnection.lo | sed
... 's|[^/]*$|.deps/&;s|\.lo$||'`; \
664 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I ../..
... -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SqliteConnection.lo -MD -MP -MF $depbase.Tpo -c -o
... SqliteConnection.lo SqliteConnection.cc && \
665 mv -f $depbase.Tpo $depbase.Plo
666 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SqliteConnection.lo -MD -MP -MF .deps/SqliteConnection.Tpo -c
... SqliteConnection.cc -fno-common -DPIC -o
... .libs/SqliteConnection.o
667 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
668 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
```

```
668... ./.../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SQLiteConnection.lo -MD -MP -MF .deps/SQLiteConnection.Tpo -c
... SQLiteConnection.cc -o SQLiteConnection.o >/dev/null 2>&1
669 depbase=`echo SQLiteResultValue.lo | sed
... 's|[^/]*$|.deps/&|;s|\.$||'`; \
670 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I ../.../..
... -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SQLiteResultValue.lo -MD -MP -MF $depbase.Tpo -c -o
... SQLiteResultValue.lo SQLiteResultValue.cc && \
671 mv -f $depbase.Tpo $depbase.Plo
672 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ./.../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SQLiteResultValue.lo -MD -MP -MF .deps/SQLiteResultValue.Tpo -c
... SQLiteResultValue.cc -fno-common -DPIC -o
... .libs/SQLiteResultValue.o
673 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
674 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ./.../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SQLiteResultValue.lo -MD -MP -MF .deps/SQLiteResultValue.Tpo -c
... SQLiteResultValue.cc -o SQLiteResultValue.o >/dev/null 2>&1
675 depbase=`echo SQLiteProvider.lo | sed
... 's|[^/]*$|.deps/&|;s|\.$||'`; \
676 /bin/sh ../../libtool --tag=CXX --mode=compile g++
... -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I ../.../..
... -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SQLiteProvider.lo -MD -MP -MF $depbase.Tpo -c -o
... SQLiteProvider.lo SQLiteProvider.cc && \
677 mv -f $depbase.Tpo $depbase.Plo
678 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ./.../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SQLiteProvider.lo -MD -MP -MF .deps/SQLiteProvider.Tpo -c
... SQLiteProvider.cc -fno-common -DPIC -o .libs/SQLiteProvider.o
679 clang: warning: argument unused during compilation:
```

```

679.. '-L/usr/local/lib' [-Wunused-command-line-argument]
680 libtool: compile: g++ -DHAVE_CONFIG_H -I. -I../.. -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... SqliteProvider.lo -MD -MP -MF .deps/SqliteProvider.Tpo -c
... SqliteProvider.cc -o SqliteProvider.o >/dev/null 2>&1
681 /bin/sh .././libtool --tag=CXX --mode=link g++ -I ../.. -I
... ../.. -Wno-deprecated-declarations -L/usr/local/lib -g -O2
... -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -I/usr/local/include -lsqlite3 -o lib_sql.la -rpath
... /usr/local/lib/apl apl-sqlite.lo Connection.lo
... SqliteArgListBuilder.lo SqliteConnection.lo
... SqliteResultValue.lo SqliteProvider.lo -lpng -lcairo -ldl -lm
... -lncurses -lcurses -lpthread -lz
682 libtool: link: g++ -dynamiclib -Wl,-undefined
... -Wl,dynamic_lookup -o .libs/lib_sql.0.dylib .libs/apl-sqlite.o
... .libs/Connection.o .libs/SqliteArgListBuilder.o
... .libs/SqliteConnection.o .libs/SqliteResultValue.o
... .libs/SqliteProvider.o -L/usr/local/lib
... /usr/local/lib/libsqlite3.dylib -lpng -lcairo -ldl -lm
... -lncurses -lcurses -lpthread -lz -g -O2 -install_name
... /usr/local/lib/apl/lib_sql.0.dylib -compatibility_version 1
... -current_version 1.0 -Wl,-single_module
683 libtool: link: (cd ".libs" && rm -f "lib_sql.dylib" && ln -s
... "lib_sql.0.dylib" "lib_sql.dylib")
684 libtool: link: ar cr .libs/lib_sql.a apl-sqlite.o Connection.o
... SqliteArgListBuilder.o SqliteConnection.o SqliteResultValue.o
... SqliteProvider.o
685 libtool: link: ranlib .libs/lib_sql.a
686 libtool: link: ( cd ".libs" && rm -f "lib_sql.la" && ln -s
... "../lib_sql.la" "lib_sql.la" )
687 Making all in workspaces
688 make[3]: Nothing to be done for `all'.
689 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-main.o -MD
... -MP -MF .deps/apl-main.Tpo -c -o apl-main.o `test -f 'main.cc'
... || echo './'`main.cc
690 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]

```

```
691 mv -f .deps/apl-main.Tpo .deps/apl-main.Po
692 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Plot_xcb.o
... -MD -MP -MF .deps/apl-Plot_xcb.Tpo -c -o apl-Plot_xcb.o `test
... -f 'Plot_xcb.cc' || echo './`Plot_xcb.cc
693 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
694 mv -f .deps/apl-Plot_xcb.Tpo .deps/apl-Plot_xcb.Po
695 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Archive.o
... -MD -MP -MF .deps/apl-Archive.Tpo -c -o apl-Archive.o `test -f
... 'Archive.cc' || echo './`Archive.cc
696 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
697 mv -f .deps/apl-Archive.Tpo .deps/apl-Archive.Po
698 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Assert.o
... -MD -MP -MF .deps/apl-Assert.Tpo -c -o apl-Assert.o `test -f
... 'Assert.cc' || echo './`Assert.cc
699 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
700 mv -f .deps/apl-Assert.Tpo .deps/apl-Assert.Po
701 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Avec.o -MD
... -MP -MF .deps/apl-Avec.Tpo -c -o apl-Avec.o `test -f 'Avec.cc'
... || echo './`Avec.cc
702 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
703 mv -f .deps/apl-Avec.Tpo .deps/apl-Avec.Po
704 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Backtrace.o
```

```
704... -MD -MP -MF .deps/apl-Backtrace.Tpo -c -o apl-Backtrace.o `test
... -f 'Backtrace.cc' || echo './`Backtrace.cc
705 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
706 mv -f .deps/apl-Backtrace.Tpo .deps/apl-Backtrace.Po
707 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_COMMA.o -MD -MP -MF .deps/apl-Bif_F12_COMMA.Tpo -c
... -o apl-Bif_F12_COMMA.o `test -f 'Bif_F12_COMMA.cc' || echo
... './`Bif_F12_COMMA.cc
708 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
709 mv -f .deps/apl-Bif_F12_COMMA.Tpo .deps/apl-Bif_F12_COMMA.Po
710 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_DOMINO.o -MD -MP -MF .deps/apl-Bif_F12_DOMINO.Tpo
... -c -o apl-Bif_F12_DOMINO.o `test -f 'Bif_F12_DOMINO.cc' || echo
... './`Bif_F12_DOMINO.cc
711 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
712 mv -f .deps/apl-Bif_F12_DOMINO.Tpo .deps/apl-Bif_F12_DOMINO.Po
713 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_INDEX_OF.o -MD -MP -MF
... .deps/apl-Bif_F12_INDEX_OF.Tpo -c -o apl-Bif_F12_INDEX_OF.o
... `test -f 'Bif_F12_INDEX_OF.cc' || echo './`Bif_F12_INDEX_OF.cc
714 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
715 mv -f .deps/apl-Bif_F12_INDEX_OF.Tpo
... .deps/apl-Bif_F12_INDEX_OF.Po
716 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_INTERVAL_INDEX.o -MD -MP -MF
```

```
716... .deps/apl-Bif_F12_INTERVAL_INDEX.Tpo -c -o
... apl-Bif_F12_INTERVAL_INDEX.o `test -f
... 'Bif_F12_INTERVAL_INDEX.cc' || echo
... './`Bif_F12_INTERVAL_INDEX.cc
717 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
718 mv -f .deps/apl-Bif_F12_INTERVAL_INDEX.Tpo
... .deps/apl-Bif_F12_INTERVAL_INDEX.Po
719 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_FORMAT.o -MD -MP -MF .deps/apl-Bif_F12_FORMAT.Tpo
... -c -o apl-Bif_F12_FORMAT.o `test -f 'Bif_F12_FORMAT.cc' || echo
... './`Bif_F12_FORMAT.cc
720 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
721 mv -f .deps/apl-Bif_F12_FORMAT.Tpo .deps/apl-Bif_F12_FORMAT.Po
722 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_PARTITION_PICK.o -MD -MP -MF
... .deps/apl-Bif_F12_PARTITION_PICK.Tpo -c -o
... apl-Bif_F12_PARTITION_PICK.o `test -f
... 'Bif_F12_PARTITION_PICK.cc' || echo
... './`Bif_F12_PARTITION_PICK.cc
723 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
724 mv -f .deps/apl-Bif_F12_PARTITION_PICK.Tpo
... .deps/apl-Bif_F12_PARTITION_PICK.Po
725 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_SORT.o -MD -MP -MF .deps/apl-Bif_F12_SORT.Tpo -c -o
... apl-Bif_F12_SORT.o `test -f 'Bif_F12_SORT.cc' || echo
... './`Bif_F12_SORT.cc
726 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
727 mv -f .deps/apl-Bif_F12_SORT.Tpo .deps/apl-Bif_F12_SORT.Po
```

```
728 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_F12_TAKE_DROP.o -MD -MP -MF
... .deps/apl-Bif_F12_TAKE_DROP.Tpo -c -o apl-Bif_F12_TAKE_DROP.o
... `test -f 'Bif_F12_TAKE_DROP.cc' || echo
... './'`Bif_F12_TAKE_DROP.cc
729 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
730 mv -f .deps/apl-Bif_F12_TAKE_DROP.Tpo
... .deps/apl-Bif_F12_TAKE_DROP.Po
731 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER1_COMMUTE.o -MD -MP -MF
... .deps/apl-Bif_OPER1_COMMUTE.Tpo -c -o apl-Bif_OPER1_COMMUTE.o
... `test -f 'Bif_OPER1_COMMUTE.cc' || echo
... './'`Bif_OPER1_COMMUTE.cc
732 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
733 mv -f .deps/apl-Bif_OPER1_COMMUTE.Tpo
... .deps/apl-Bif_OPER1_COMMUTE.Po
734 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER1_EACH.o -MD -MP -MF .deps/apl-Bif_OPER1_EACH.Tpo
... -c -o apl-Bif_OPER1_EACH.o `test -f 'Bif_OPER1_EACH.cc' || echo
... './'`Bif_OPER1_EACH.cc
735 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
736 mv -f .deps/apl-Bif_OPER1_EACH.Tpo .deps/apl-Bif_OPER1_EACH.Po
737 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER2_POWER.o -MD -MP -MF .deps/apl-Bif_OPER2_POWER.Tpo
... -c -o apl-Bif_OPER2_POWER.o `test -f 'Bif_OPER2_POWER.cc' ||
... echo './'`Bif_OPER2_POWER.cc
```

```
738 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
739 mv -f .deps/apl-Bif_OPER2_POWER.Tpo
... .deps/apl-Bif_OPER2_POWER.Po
740 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER2_INNER.o -MD -MP -MF .deps/apl-Bif_OPER2_INNER.Tpo
... -c -o apl-Bif_OPER2_INNER.o `test -f 'Bif_OPER2_INNER.cc' ||
... echo './`Bif_OPER2_INNER.cc
741 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
742 mv -f .deps/apl-Bif_OPER2_INNER.Tpo
... .deps/apl-Bif_OPER2_INNER.Po
743 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER2_OUTER.o -MD -MP -MF .deps/apl-Bif_OPER2_OUTER.Tpo
... -c -o apl-Bif_OPER2_OUTER.o `test -f 'Bif_OPER2_OUTER.cc' ||
... echo './`Bif_OPER2_OUTER.cc
744 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
745 mv -f .deps/apl-Bif_OPER2_OUTER.Tpo
... .deps/apl-Bif_OPER2_OUTER.Po
746 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER2_RANK.o -MD -MP -MF .deps/apl-Bif_OPER2_RANK.Tpo
... -c -o apl-Bif_OPER2_RANK.o `test -f 'Bif_OPER2_RANK.cc' || echo
... './`Bif_OPER2_RANK.cc
747 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
748 mv -f .deps/apl-Bif_OPER2_RANK.Tpo .deps/apl-Bif_OPER2_RANK.Po
749 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER1_REDUCE.o -MD -MP -MF
```

```
749... .deps/apl-Bif_OPER1_REDUCE.Tpo -c -o apl-Bif_OPER1_REDUCE.o
... `test -f 'Bif_OPER1_REDUCE.cc' || echo './`Bif_OPER1_REDUCE.cc
750 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
751 mv -f .deps/apl-Bif_OPER1_REDUCE.Tpo
... .deps/apl-Bif_OPER1_REDUCE.Po
752 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Bif_OPER1_SCAN.o -MD -MP -MF .deps/apl-Bif_OPER1_SCAN.Tpo
... -c -o apl-Bif_OPER1_SCAN.o `test -f 'Bif_OPER1_SCAN.cc' || echo
... './`Bif_OPER1_SCAN.cc
753 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
754 mv -f .deps/apl-Bif_OPER1_SCAN.Tpo .deps/apl-Bif_OPER1_SCAN.Po
755 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-CDR.o -MD
... -MP -MF .deps/apl-CDR.Tpo -c -o apl-CDR.o `test -f 'CDR.cc' ||
... echo './`CDR.cc
756 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
757 mv -f .deps/apl-CDR.Tpo .deps/apl-CDR.Po
758 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Cell.o -MD
... -MP -MF .deps/apl-Cell.Tpo -c -o apl-Cell.o `test -f 'Cell.cc'
... || echo './`Cell.cc
759 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
760 mv -f .deps/apl-Cell.Tpo .deps/apl-Cell.Po
761 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Doxy.o -MD
... -MP -MF .deps/apl-Doxy.Tpo -c -o apl-Doxy.o `test -f 'Doxy.cc'
... || echo './`Doxy.cc
762 clang: warning: argument unused during compilation:
```

```
762... '-L/usr/local/lib' [-Wunused-command-line-argument]
763 mv -f .deps/apl-Doxy.Tpo .deps/apl-Doxy.Po
764 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-CharCell.o
... -MD -MP -MF .deps/apl-CharCell.Tpo -c -o apl-CharCell.o `test
... -f 'CharCell.cc' || echo './`CharCell.cc
765 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
766 mv -f .deps/apl-CharCell.Tpo .deps/apl-CharCell.Po
767 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Command.o
... -MD -MP -MF .deps/apl-Command.Tpo -c -o apl-Command.o `test -f
... 'Command.cc' || echo './`Command.cc
768 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
769 mv -f .deps/apl-Command.Tpo .deps/apl-Command.Po
770 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Common.o
... -MD -MP -MF .deps/apl-Common.Tpo -c -o apl-Common.o `test -f
... 'Common.cc' || echo './`Common.cc
771 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
772 mv -f .deps/apl-Common.Tpo .deps/apl-Common.Po
773 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-ComplexCell.o -MD -MP -MF .deps/apl-ComplexCell.Tpo -c -o
... apl-ComplexCell.o `test -f 'ComplexCell.cc' || echo
... './`ComplexCell.cc
774 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
775 mv -f .deps/apl-ComplexCell.Tpo .deps/apl-ComplexCell.Po
776 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
```

```
776... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-DerivedFunction.o -MD -MP -MF .deps/apl-DerivedFunction.Tpo
... -c -o apl-DerivedFunction.o `test -f 'DerivedFunction.cc' ||
... echo './'`DerivedFunction.cc
777 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
778 mv -f .deps/apl-DerivedFunction.Tpo
... .deps/apl-DerivedFunction.Po
779 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-DiffOut.o
... -MD -MP -MF .deps/apl-DiffOut.Tpo -c -o apl-DiffOut.o `test -f
... 'DiffOut.cc' || echo './'`DiffOut.cc
780 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
781 mv -f .deps/apl-DiffOut.Tpo .deps/apl-DiffOut.Po
782 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-DynamicObject.o -MD -MP -MF .deps/apl-DynamicObject.Tpo -c
... -o apl-DynamicObject.o `test -f 'DynamicObject.cc' || echo
... './'`DynamicObject.cc
783 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
784 mv -f .deps/apl-DynamicObject.Tpo .deps/apl-DynamicObject.Po
785 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Error.o -MD
... -MP -MF .deps/apl-Error.Tpo -c -o apl-Error.o `test -f
... 'Error.cc' || echo './'`Error.cc
786 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
787 mv -f .deps/apl-Error.Tpo .deps/apl-Error.Po
788 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
```

```
788... apl-Executable.o -MD -MP -MF .deps/apl-Executable.Tpo -c -o
... apl-Executable.o `test -f 'Executable.cc' || echo
... './`Executable.cc
789 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
790 mv -f .deps/apl-Executable.Tpo .deps/apl-Executable.Po
791 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-FloatCell.o
... -MD -MP -MF .deps/apl-FloatCell.Tpo -c -o apl-FloatCell.o `test
... -f 'FloatCell.cc' || echo './`FloatCell.cc
792 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
793 mv -f .deps/apl-FloatCell.Tpo .deps/apl-FloatCell.Po
794 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Function.o
... -MD -MP -MF .deps/apl-Function.Tpo -c -o apl-Function.o `test
... -f 'Function.cc' || echo './`Function.cc
795 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
796 mv -f .deps/apl-Function.Tpo .deps/apl-Function.Po
797 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Id.o -MD
... -MP -MF .deps/apl-Id.Tpo -c -o apl-Id.o `test -f 'Id.cc' ||
... echo './`Id.cc
798 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
799 mv -f .deps/apl-Id.Tpo .deps/apl-Id.Po
800 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-IndexExpr.o
... -MD -MP -MF .deps/apl-IndexExpr.Tpo -c -o apl-IndexExpr.o `test
... -f 'IndexExpr.cc' || echo './`IndexExpr.cc
801 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
```

```
802 mv -f .deps/apl-IndexExpr.Tpo .deps/apl-IndexExpr.Po
803 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-IndexIterator.o -MD -MP -MF .deps/apl-IndexIterator.Tpo -c
... -o apl-IndexIterator.o `test -f 'IndexIterator.cc' || echo
... './`IndexIterator.cc
804 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
805 mv -f .deps/apl-IndexIterator.Tpo .deps/apl-IndexIterator.Po
806 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-InputFile.o
... -MD -MP -MF .deps/apl-InputFile.Tpo -c -o apl-InputFile.o `test
... -f 'InputFile.cc' || echo './`InputFile.cc
807 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
808 mv -f .deps/apl-InputFile.Tpo .deps/apl-InputFile.Po
809 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-IntCell.o
... -MD -MP -MF .deps/apl-IntCell.Tpo -c -o apl-IntCell.o `test -f
... 'IntCell.cc' || echo './`IntCell.cc
810 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
811 mv -f .deps/apl-IntCell.Tpo .deps/apl-IntCell.Po
812 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-IO_Files.o
... -MD -MP -MF .deps/apl-IO_Files.Tpo -c -o apl-IO_Files.o `test
... -f 'IO_Files.cc' || echo './`IO_Files.cc
813 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
814 mv -f .deps/apl-IO_Files.Tpo .deps/apl-IO_Files.Po
815 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
```

```
815... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-LApack.o
... -MD -MP -MF .deps/apl-LApack.Tpo -c -o apl-LApack.o `test -f
... 'LApack.cc' || echo './'`LApack.cc
816 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
817 mv -f .deps/apl-LApack.Tpo .deps/apl-LApack.Po
818 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-LibPaths.o
... -MD -MP -MF .deps/apl-LibPaths.Tpo -c -o apl-LibPaths.o `test
... -f 'LibPaths.cc' || echo './'`LibPaths.cc
819 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
820 mv -f .deps/apl-LibPaths.Tpo .deps/apl-LibPaths.Po
821 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-LineInput.o
... -MD -MP -MF .deps/apl-LineInput.Tpo -c -o apl-LineInput.o `test
... -f 'LineInput.cc' || echo './'`LineInput.cc
822 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
823 mv -f .deps/apl-LineInput.Tpo .deps/apl-LineInput.Po
824 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Logging.o
... -MD -MP -MF .deps/apl-Logging.Tpo -c -o apl-Logging.o `test -f
... 'Logging.cc' || echo './'`Logging.cc
825 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
826 mv -f .deps/apl-Logging.Tpo .deps/apl-Logging.Po
827 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-LvalCell.o
... -MD -MP -MF .deps/apl-LvalCell.Tpo -c -o apl-LvalCell.o `test
... -f 'LvalCell.cc' || echo './'`LvalCell.cc
828 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
```

```
829 mv -f .deps/apl-LvalCell.Tpo .deps/apl-LvalCell.Po
830 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Malloc_hooks.o -MD -MP -MF .deps/apl-Malloc_hooks.Tpo -c -o
... apl-Malloc_hooks.o `test -f 'Malloc_hooks.cc' || echo
... './`Malloc_hooks.cc
831 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
832 mv -f .deps/apl-Malloc_hooks.Tpo .deps/apl-Malloc_hooks.Po
833 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Nabla.o -MD
... -MP -MF .deps/apl-Nabla.Tpo -c -o apl-Nabla.o `test -f
... 'Nabla.cc' || echo './`Nabla.cc
834 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
835 mv -f .deps/apl-Nabla.Tpo .deps/apl-Nabla.Po
836 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Macro.o -MD
... -MP -MF .deps/apl-Macro.Tpo -c -o apl-Macro.o `test -f
... 'Macro.cc' || echo './`Macro.cc
837 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
838 mv -f .deps/apl-Macro.Tpo .deps/apl-Macro.Po
839 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Missing_Libraries.o -MD -MP -MF
... .deps/apl-Missing_Libraries.Tpo -c -o apl-Missing_Libraries.o
... `test -f 'Missing_Libraries.cc' || echo
... './`Missing_Libraries.cc
840 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
841 mv -f .deps/apl-Missing_Libraries.Tpo
... .deps/apl-Missing_Libraries.Po
```

```
842 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-NamedObject.o -MD -MP -MF .deps/apl-NamedObject.Tpo -c -o
... apl-NamedObject.o `test -f 'NamedObject.cc' || echo
... './'`NamedObject.cc
843 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
844 mv -f .deps/apl-NamedObject.Tpo .deps/apl-NamedObject.Po
845 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-NativeFunction.o -MD -MP -MF .deps/apl-NativeFunction.Tpo
... -c -o apl-NativeFunction.o `test -f 'NativeFunction.cc' || echo
... './'`NativeFunction.cc
846 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
847 mv -f .deps/apl-NativeFunction.Tpo .deps/apl-NativeFunction.Po
848 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-NumericCell.o -MD -MP -MF .deps/apl-NumericCell.Tpo -c -o
... apl-NumericCell.o `test -f 'NumericCell.cc' || echo
... './'`NumericCell.cc
849 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
850 mv -f .deps/apl-NumericCell.Tpo .deps/apl-NumericCell.Po
851 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Output.o
... -MD -MP -MF .deps/apl-Output.Tpo -c -o apl-Output.o `test -f
... 'Output.cc' || echo './'`Output.cc
852 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
853 mv -f .deps/apl-Output.Tpo .deps/apl-Output.Po
854 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
```

```
854... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Parallel.o
... -MD -MP -MF .deps/apl-Parallel.Tpo -c -o apl-Parallel.o `test
... -f 'Parallel.cc' || echo './'`Parallel.cc
855 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
856 mv -f .deps/apl-Parallel.Tpo .deps/apl-Parallel.Po
857 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Parser.o
... -MD -MP -MF .deps/apl-Parser.Tpo -c -o apl-Parser.o `test -f
... 'Parser.cc' || echo './'`Parser.cc
858 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
859 mv -f .deps/apl-Parser.Tpo .deps/apl-Parser.Po
860 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Performance.o -MD -MP -MF .deps/apl-Performance.Tpo -c -o
... apl-Performance.o `test -f 'Performance.cc' || echo
... './'`Performance.cc
861 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
862 mv -f .deps/apl-Performance.Tpo .deps/apl-Performance.Po
863 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-PointerCell.o -MD -MP -MF .deps/apl-PointerCell.Tpo -c -o
... apl-PointerCell.o `test -f 'PointerCell.cc' || echo
... './'`PointerCell.cc
864 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
865 mv -f .deps/apl-PointerCell.Tpo .deps/apl-PointerCell.Po
866 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Prefix.o
... -MD -MP -MF .deps/apl-Prefix.Tpo -c -o apl-Prefix.o `test -f
```

```
866.. 'Prefix.cc' || echo './'`Prefix.cc
867 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
868 mv -f .deps/apl-Prefix.Tpo .deps/apl-Prefix.Po
869 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Plot_line_properties.o -MD -MP -MF
... .deps/apl-Plot_line_properties.Tpo -c -o
... apl-Plot_line_properties.o `test -f 'Plot_line_properties.cc'
... || echo './'`Plot_line_properties.cc
870 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
871 mv -f .deps/apl-Plot_line_properties.Tpo
... .deps/apl-Plot_line_properties.Po
872 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Plot_data.o
... -MD -MP -MF .deps/apl-Plot_data.Tpo -c -o apl-Plot_data.o `test
... -f 'Plot_data.cc' || echo './'`Plot_data.cc
873 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
874 mv -f .deps/apl-Plot_data.Tpo .deps/apl-Plot_data.Po
875 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Plot_window_properties.o -MD -MP -MF
... .deps/apl-Plot_window_properties.Tpo -c -o
... apl-Plot_window_properties.o `test -f
... 'Plot_window_properties.cc' || echo
... './'`Plot_window_properties.cc
876 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
877 mv -f .deps/apl-Plot_window_properties.Tpo
... .deps/apl-Plot_window_properties.Po
878 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
```

```
878... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-PrimitiveFunction.o -MD -MP -MF
... .deps/apl-PrimitiveFunction.Tpo -c -o apl-PrimitiveFunction.o
... `test -f 'PrimitiveFunction.cc' || echo
... './'`PrimitiveFunction.cc
879 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
880 mv -f .deps/apl-PrimitiveFunction.Tpo
... .deps/apl-PrimitiveFunction.Po
881 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-PrintBuffer.o -MD -MP -MF .deps/apl-PrintBuffer.Tpo -c -o
... apl-PrintBuffer.o `test -f 'PrintBuffer.cc' || echo
... './'`PrintBuffer.cc
882 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
883 mv -f .deps/apl-PrintBuffer.Tpo .deps/apl-PrintBuffer.Po
884 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-QuadFunction.o -MD -MP -MF .deps/apl-QuadFunction.Tpo -c -o
... apl-QuadFunction.o `test -f 'QuadFunction.cc' || echo
... './'`QuadFunction.cc
885 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
886 mv -f .deps/apl-QuadFunction.Tpo .deps/apl-QuadFunction.Po
887 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-ProcessorID.o -MD -MP -MF .deps/apl-ProcessorID.Tpo -c -o
... apl-ProcessorID.o `test -f 'ProcessorID.cc' || echo
... './'`ProcessorID.cc
888 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
889 mv -f .deps/apl-ProcessorID.Tpo .deps/apl-ProcessorID.Po
890 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
```

```
890... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_CR.o
... -MD -MP -MF .deps/apl-Quad_CR.Tpo -c -o apl-Quad_CR.o `test -f
... 'Quad_CR.cc' || echo './`Quad_CR.cc
891 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
892 mv -f .deps/apl-Quad_CR.Tpo .deps/apl-Quad_CR.Po
893 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_DLX.o
... -MD -MP -MF .deps/apl-Quad_DLX.Tpo -c -o apl-Quad_DLX.o `test
... -f 'Quad_DLX.cc' || echo './`Quad_DLX.cc
894 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
895 mv -f .deps/apl-Quad_DLX.Tpo .deps/apl-Quad_DLX.Po
896 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_FFT.o
... -MD -MP -MF .deps/apl-Quad_FFT.Tpo -c -o apl-Quad_FFT.o `test
... -f 'Quad_FFT.cc' || echo './`Quad_FFT.cc
897 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
898 mv -f .deps/apl-Quad_FFT.Tpo .deps/apl-Quad_FFT.Po
899 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_FIO.o
... -MD -MP -MF .deps/apl-Quad_FIO.Tpo -c -o apl-Quad_FIO.o `test
... -f 'Quad_FIO.cc' || echo './`Quad_FIO.cc
900 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
901 mv -f .deps/apl-Quad_FIO.Tpo .deps/apl-Quad_FIO.Po
902 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_FX.o
... -MD -MP -MF .deps/apl-Quad_FX.Tpo -c -o apl-Quad_FX.o `test -f
... 'Quad_FX.cc' || echo './`Quad_FX.cc
903 clang: warning: argument unused during compilation:
```

```
903.. '-L/usr/local/lib' [-Wunused-command-line-argument]
904 mv -f .deps/apl-Quad_FX.Tpo .deps/apl-Quad_FX.Po
905 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_GTK.o
... -MD -MP -MF .deps/apl-Quad_GTK.Tpo -c -o apl-Quad_GTK.o `test
... -f 'Quad_GTK.cc' || echo './`Quad_GTK.cc
906 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
907 mv -f .deps/apl-Quad_GTK.Tpo .deps/apl-Quad_GTK.Po
908 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_JSON.o
... -MD -MP -MF .deps/apl-Quad_JSON.Tpo -c -o apl-Quad_JSON.o `test
... -f 'Quad_JSON.cc' || echo './`Quad_JSON.cc
909 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
910 mv -f .deps/apl-Quad_JSON.Tpo .deps/apl-Quad_JSON.Po
911 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_MAP.o
... -MD -MP -MF .deps/apl-Quad_MAP.Tpo -c -o apl-Quad_MAP.o `test
... -f 'Quad_MAP.cc' || echo './`Quad_MAP.cc
912 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
913 mv -f .deps/apl-Quad_MAP.Tpo .deps/apl-Quad_MAP.Po
914 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_PLOT.o
... -MD -MP -MF .deps/apl-Quad_PLOT.Tpo -c -o apl-Quad_PLOT.o `test
... -f 'Quad_PLOT.cc' || echo './`Quad_PLOT.cc
915 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
916 mv -f .deps/apl-Quad_PLOT.Tpo .deps/apl-Quad_PLOT.Po
917 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
```

```
917... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_PNG.o
... -MD -MP -MF .deps/apl-Quad_PNG.Tpo -c -o apl-Quad_PNG.o `test
... -f 'Quad_PNG.cc' || echo './`Quad_PNG.cc
918 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
919 mv -f .deps/apl-Quad_PNG.Tpo .deps/apl-Quad_PNG.Po
920 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_RE.o
... -MD -MP -MF .deps/apl-Quad_RE.Tpo -c -o apl-Quad_RE.o `test -f
... 'Quad_RE.cc' || echo './`Quad_RE.cc
921 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
922 mv -f .deps/apl-Quad_RE.Tpo .deps/apl-Quad_RE.Po
923 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_RL.o
... -MD -MP -MF .deps/apl-Quad_RL.Tpo -c -o apl-Quad_RL.o `test -f
... 'Quad_RL.cc' || echo './`Quad_RL.cc
924 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
925 mv -f .deps/apl-Quad_RL.Tpo .deps/apl-Quad_RL.Po
926 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_RVAL.o
... -MD -MP -MF .deps/apl-Quad_RVAL.Tpo -c -o apl-Quad_RVAL.o `test
... -f 'Quad_RVAL.cc' || echo './`Quad_RVAL.cc
927 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
928 mv -f .deps/apl-Quad_RVAL.Tpo .deps/apl-Quad_RVAL.Po
929 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_SQL.o
... -MD -MP -MF .deps/apl-Quad_SQL.Tpo -c -o apl-Quad_SQL.o `test
... -f 'Quad_SQL.cc' || echo './`Quad_SQL.cc
930 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
```

```
931 mv -f .deps/apl-Quad_SQL.Tpo .deps/apl-Quad_SQL.Po
932 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_SVx.o
... -MD -MP -MF .deps/apl-Quad_SVx.Tpo -c -o apl-Quad_SVx.o `test
... -f 'Quad_SVx.cc' || echo './`Quad_SVx.cc
933 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
934 mv -f .deps/apl-Quad_SVx.Tpo .deps/apl-Quad_SVx.Po
935 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_TF.o
... -MD -MP -MF .deps/apl-Quad_TF.Tpo -c -o apl-Quad_TF.o `test -f
... 'Quad_TF.cc' || echo './`Quad_TF.cc
936 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
937 mv -f .deps/apl-Quad_TF.Tpo .deps/apl-Quad_TF.Po
938 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_WA.o
... -MD -MP -MF .deps/apl-Quad_WA.Tpo -c -o apl-Quad_WA.o `test -f
... 'Quad_WA.cc' || echo './`Quad_WA.cc
939 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
940 mv -f .deps/apl-Quad_WA.Tpo .deps/apl-Quad_WA.Po
941 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Quad_XML.o
... -MD -MP -MF .deps/apl-Quad_XML.Tpo -c -o apl-Quad_XML.o `test
... -f 'Quad_XML.cc' || echo './`Quad_XML.cc
942 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
943 mv -f .deps/apl-Quad_XML.Tpo .deps/apl-Quad_XML.Po
944 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-RealCell.o
```

```
944... -MD -MP -MF .deps/apl-RealCell.Tpo -c -o apl-RealCell.o `test
... -f 'RealCell.cc' || echo './`RealCell.cc
945 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
946 mv -f .deps/apl-RealCell.Tpo .deps/apl-RealCell.Po
947 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-sbrk.o -MD
... -MP -MF .deps/apl-sbrk.Tpo -c -o apl-sbrk.o `test -f 'sbrk.cc'
... || echo './`sbrk.cc
948 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
949 mv -f .deps/apl-sbrk.Tpo .deps/apl-sbrk.Po
950 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Shape.o -MD
... -MP -MF .deps/apl-Shape.Tpo -c -o apl-Shape.o `test -f
... 'Shape.cc' || echo './`Shape.cc
951 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
952 mv -f .deps/apl-Shape.Tpo .deps/apl-Shape.Po
953 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-ScalarFunction.o -MD -MP -MF .deps/apl-ScalarFunction.Tpo
... -c -o apl-ScalarFunction.o `test -f 'ScalarFunction.cc' || echo
... './`ScalarFunction.cc
954 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
955 mv -f .deps/apl-ScalarFunction.Tpo .deps/apl-ScalarFunction.Po
956 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Security.o
... -MD -MP -MF .deps/apl-Security.Tpo -c -o apl-Security.o `test
... -f 'Security.cc' || echo './`Security.cc
957 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
```

```
958 mv -f .deps/apl-Security.Tpo .deps/apl-Security.Po
959 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-StateIndicator.o -MD -MP -MF .deps/apl-StateIndicator.Tpo
... -c -o apl-StateIndicator.o `test -f 'StateIndicator.cc' || echo
... './'`StateIndicator.cc
960 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
961 mv -f .deps/apl-StateIndicator.Tpo .deps/apl-StateIndicator.Po
962 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Svar_DB.o
... -MD -MP -MF .deps/apl-Svar_DB.Tpo -c -o apl-Svar_DB.o `test -f
... 'Svar_DB.cc' || echo './'`Svar_DB.cc
963 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
964 mv -f .deps/apl-Svar_DB.Tpo .deps/apl-Svar_DB.Po
965 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Svar_record.o -MD -MP -MF .deps/apl-Svar_record.Tpo -c -o
... apl-Svar_record.o `test -f 'Svar_record.cc' || echo
... './'`Svar_record.cc
966 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
967 mv -f .deps/apl-Svar_record.Tpo .deps/apl-Svar_record.Po
968 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Symbol.o
... -MD -MP -MF .deps/apl-Symbol.Tpo -c -o apl-Symbol.o `test -f
... 'Symbol.cc' || echo './'`Symbol.cc
969 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
970 mv -f .deps/apl-Symbol.Tpo .deps/apl-Symbol.Po
971 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
```

```
971... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-SymbolTable.o -MD -MP -MF .deps/apl-SymbolTable.Tpo -c -o
... apl-SymbolTable.o `test -f 'SymbolTable.cc' || echo
... './`SymbolTable.cc
972 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
973 mv -f .deps/apl-SymbolTable.Tpo .deps/apl-SymbolTable.Po
974 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-SystemVariable.o -MD -MP -MF .deps/apl-SystemVariable.Tpo
... -c -o apl-SystemVariable.o `test -f 'SystemVariable.cc' || echo
... './`SystemVariable.cc
975 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
976 mv -f .deps/apl-SystemVariable.Tpo .deps/apl-SystemVariable.Po
977 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-TabExpansion.o -MD -MP -MF .deps/apl-TabExpansion.Tpo -c -o
... apl-TabExpansion.o `test -f 'TabExpansion.cc' || echo
... './`TabExpansion.cc
978 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
979 mv -f .deps/apl-TabExpansion.Tpo .deps/apl-TabExpansion.Po
980 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-Thread_context.o -MD -MP -MF .deps/apl-Thread_context.Tpo
... -c -o apl-Thread_context.o `test -f 'Thread_context.cc' || echo
... './`Thread_context.cc
981 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
982 mv -f .deps/apl-Thread_context.Tpo .deps/apl-Thread_context.Po
983 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
```

```
983... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Token.o -MD
... -MP -MF .deps/apl-Token.Tpo -c -o apl-Token.o `test -f
... 'Token.cc' || echo './`Token.cc
984 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
985 mv -f .deps/apl-Token.Tpo .deps/apl-Token.Po
986 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Tokenizer.o
... -MD -MP -MF .deps/apl-Tokenizer.Tpo -c -o apl-Tokenizer.o `test
... -f 'Tokenizer.cc' || echo './`Tokenizer.cc
987 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
988 mv -f .deps/apl-Tokenizer.Tpo .deps/apl-Tokenizer.Po
989 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-UCS_string.o -MD -MP -MF .deps/apl-UCS_string.Tpo -c -o
... apl-UCS_string.o `test -f 'UCS_string.cc' || echo
... './`UCS_string.cc
990 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
991 mv -f .deps/apl-UCS_string.Tpo .deps/apl-UCS_string.Po
992 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-UCS_string_vector.o -MD -MP -MF
... .deps/apl-UCS_string_vector.Tpo -c -o apl-UCS_string_vector.o
... `test -f 'UCS_string_vector.cc' || echo
... './`UCS_string_vector.cc
993 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
994 mv -f .deps/apl-UCS_string_vector.Tpo
... .deps/apl-UCS_string_vector.Po
995 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
```

```
995... apl-UserFunction.o -MD -MP -MF .deps/apl-UserFunction.Tpo -c -o
... apl-UserFunction.o `test -f 'UserFunction.cc' || echo
... './`UserFunction.cc
996 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
997 mv -f .deps/apl-UserFunction.Tpo .deps/apl-UserFunction.Po
998 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-UserFunction_header.o -MD -MP -MF
... .deps/apl-UserFunction_header.Tpo -c -o
... apl-UserFunction_header.o `test -f 'UserFunction_header.cc' ||
... echo './`UserFunction_header.cc
999 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1000 mv -f .deps/apl-UserFunction_header.Tpo
... .deps/apl-UserFunction_header.Po
1001 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-UserPreferences.o -MD -MP -MF .deps/apl-UserPreferences.Tpo
... -c -o apl-UserPreferences.o `test -f 'UserPreferences.cc' ||
... echo './`UserPreferences.cc
1002 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1003 mv -f .deps/apl-UserPreferences.Tpo
... .deps/apl-UserPreferences.Po
1004 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-UTF8_string.o -MD -MP -MF .deps/apl-UTF8_string.Tpo -c -o
... apl-UTF8_string.o `test -f 'UTF8_string.cc' || echo
... './`UTF8_string.cc
1005 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1006 mv -f .deps/apl-UTF8_string.Tpo .deps/apl-UTF8_string.Po
1007 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
```

```
1007... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Value.o -MD
... -MP -MF .deps/apl-Value.Tpo -c -o apl-Value.o `test -f
... 'Value.cc' || echo './`Value.cc
1008 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1009 mv -f .deps/apl-Value.Tpo .deps/apl-Value.Po
1010 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-ValueHistory.o -MD -MP -MF .deps/apl-ValueHistory.Tpo -c -o
... apl-ValueHistory.o `test -f 'ValueHistory.cc' || echo
... './`ValueHistory.cc
1011 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1012 mv -f .deps/apl-ValueHistory.Tpo .deps/apl-ValueHistory.Po
1013 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl-Workspace.o
... -MD -MP -MF .deps/apl-Workspace.Tpo -c -o apl-Workspace.o `test
... -f 'Workspace.cc' || echo './`Workspace.cc
1014 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1015 mv -f .deps/apl-Workspace.Tpo .deps/apl-Workspace.Po
1016 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... apl-static_Objects.o -MD -MP -MF .deps/apl-static_Objects.Tpo
... -c -o apl-static_Objects.o `test -f 'static_Objects.cc' || echo
... './`static_Objects.cc
1017 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1018 mv -f .deps/apl-static_Objects.Tpo .deps/apl-static_Objects.Po
1019 g++ -DHAVE_CONFIG_H -I. -I..    -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib      -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... sql/apl-SqliteArgListBuilder.o -MD -MP -MF
```

```
1019.. sql/.deps/apl-SqliteArgListBuilder.Tpo -c -o
... sql/apl-SqliteArgListBuilder.o `test -f
... 'sql/SqliteArgListBuilder.cc' || echo
... './`sql/SqliteArgListBuilder.cc
1020 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1021 mv -f sql/.deps/apl-SqliteArgListBuilder.Tpo
... sql/.deps/apl-SqliteArgListBuilder.Po
1022 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... sql/apl-SqliteConnection.o -MD -MP -MF
... sql/.deps/apl-SqliteConnection.Tpo -c -o
... sql/apl-SqliteConnection.o `test -f 'sql/SqliteConnection.cc'
... || echo './`sql/SqliteConnection.cc
1023 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1024 mv -f sql/.deps/apl-SqliteConnection.Tpo
... sql/.deps/apl-SqliteConnection.Po
1025 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... sql/apl-SqliteResultValue.o -MD -MP -MF
... sql/.deps/apl-SqliteResultValue.Tpo -c -o
... sql/apl-SqliteResultValue.o `test -f 'sql/SqliteResultValue.cc'
... || echo './`sql/SqliteResultValue.cc
1026 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1027 mv -f sql/.deps/apl-SqliteResultValue.Tpo
... sql/.deps/apl-SqliteResultValue.Po
1028 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... sql/apl-SqliteProvider.o -MD -MP -MF
... sql/.deps/apl-SqliteProvider.Tpo -c -o sql/apl-SqliteProvider.o
... `test -f 'sql/SqliteProvider.cc' || echo
... './`sql/SqliteProvider.cc
1029 clang: warning: argument unused during compilation:
```

```
1029.. '-L/usr/local/lib' [-Wunused-command-line-argument]
1030 mv -f sql/.deps/apl-SqliteProvider.Tpo
... sql/.deps/apl-SqliteProvider.Po
1031 g++ -DHAVE_CONFIG_H -I. -I.. -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT
... sql/apl-Connection.o -MD -MP -MF sql/.deps/apl-Connection.Tpo
... -c -o sql/apl-Connection.o `test -f 'sql/Connection.cc' || echo
... './`sql/Connection.cc
1032 clang: warning: argument unused during compilation:
... '-L/usr/local/lib' [-Wunused-command-line-argument]
1033 mv -f sql/.deps/apl-Connection.Tpo sql/.deps/apl-Connection.Po
1034 /bin/sh ../libtool --tag=CXX --mode=link g++ -Wall -I sql
... -I /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -L/usr/local/lib -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -export-dynamic
... -I/usr/local/include -lsqlite3 -o apl apl-main.o
... apl-Plot_xcb.o apl-Archive.o apl-Assert.o apl-Avec.o
... apl-Backtrace.o apl-Bif_F12_COMMA.o apl-Bif_F12_DOMINO.o
... apl-Bif_F12_INDEX_OF.o apl-Bif_F12_INTERVAL_INDEX.o
... apl-Bif_F12_FORMAT.o apl-Bif_F12_PARTITION_PICK.o
... apl-Bif_F12_SORT.o apl-Bif_F12_TAKE_DROP.o
... apl-Bif_OPER1_COMMUTE.o apl-Bif_OPER1_EACH.o
... apl-Bif_OPER2_POWER.o apl-Bif_OPER2_INNER.o
... apl-Bif_OPER2_OUTER.o apl-Bif_OPER2_RANK.o
... apl-Bif_OPER1_REDUCE.o apl-Bif_OPER1_SCAN.o apl-CDR.o
... apl-Cell.o apl-Doxy.o apl-CharCell.o apl-Command.o apl-Common.o
... apl-ComplexCell.o apl-DerivedFunction.o apl-DiffOut.o
... apl-DynamicObject.o apl-Error.o apl-Executable.o
... apl-FloatCell.o apl-Function.o apl-Id.o apl-IndexExpr.o
... apl-IndexIterator.o apl-InputFile.o apl-IntCell.o
... apl-IO_Files.o apl-LApack.o apl-LibPaths.o apl-LineInput.o
... apl-Logging.o apl-LvalCell.o apl-Malloc_hooks.o apl-Nabla.o
... apl-Macro.o apl-Missing_Libraries.o apl-NamedObject.o
... apl-NativeFunction.o apl-NumericCell.o apl-Output.o
... apl-Parallel.o apl-Parser.o apl-Performance.o apl-PointerCell.o
... apl-Prefix.o apl-Plot_line_properties.o apl-Plot_data.o
... apl-Plot_window_properties.o apl-PrimitiveFunction.o
... apl-PrintBuffer.o apl-QuadFunction.o apl-ProcessorID.o
... apl-Quad_CR.o apl-Quad_DLX.o apl-Quad_FFT.o apl-Quad_FIO.o
```

```
1034... apl-Quad_FX.o apl-Quad_GTK.o apl-Quad_JSON.o apl-Quad_MAP.o
... apl-Quad_PLOT.o apl-Quad_PNG.o apl-Quad_RE.o apl-Quad_RL.o
... apl-Quad_RVAL.o apl-Quad_SQL.o apl-Quad_SVx.o apl-Quad_TF.o
... apl-Quad_WA.o apl-Quad_XML.o apl-RealCell.o apl-sbrk.o
... apl-Shape.o apl-ScalarFunction.o apl-Security.o
... apl-StateIndicator.o apl-Svar_DB.o apl-Svar_record.o
... apl-Symbol.o apl-SymbolTable.o apl-SystemVariable.o
... apl-TabExpansion.o apl-Thread_context.o apl-Token.o
... apl-Tokenizer.o apl-UCS_string.o apl-UCS_string_vector.o
... apl-UserFunction.o apl-UserFunction_header.o
... apl-UserPreferences.o apl-UTF8_string.o apl-Value.o
... apl-ValueHistory.o apl-Workspace.o apl-static_Objects.o
... sql/apl-SqliteArgListBuilder.o sql/apl-SqliteConnection.o
... sql/apl-SqliteResultValue.o sql/apl-SqliteProvider.o
... sql/apl-Connection.o -lpng -lcairo -ldl -lm -lncurses
... -lcurses -lpthread -lz -lpng -lcairo -ldl -lm -lncurses
... -lcurses -lpthread -lz
1035 libtool: link: g++ -Wall -I sql -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk
... -I/usr/local/include -o apl apl-main.o apl-Plot_xcb.o
... apl-Archive.o apl-Assert.o apl-Avec.o apl-Backtrace.o
... apl-Bif_F12_COMMA.o apl-Bif_F12_DOMINO.o apl-Bif_F12_INDEX_OF.o
... apl-Bif_F12_INTERVAL_INDEX.o apl-Bif_F12_FORMAT.o
... apl-Bif_F12_PARTITION_PICK.o apl-Bif_F12_SORT.o
... apl-Bif_F12_TAKE_DROP.o apl-Bif_OPER1_COMMUTE.o
... apl-Bif_OPER1_EACH.o apl-Bif_OPER2_POWER.o
... apl-Bif_OPER2_INNER.o apl-Bif_OPER2_OUTER.o
... apl-Bif_OPER2_RANK.o apl-Bif_OPER1_REDUCE.o
... apl-Bif_OPER1_SCAN.o apl-CDR.o apl-Cell.o apl-Doxy.o
... apl-CharCell.o apl-Command.o apl-Common.o apl-ComplexCell.o
... apl-DerivedFunction.o apl-DiffOut.o apl-DynamicObject.o
... apl-Error.o apl-Executable.o apl-FloatCell.o apl-Function.o
... apl-Id.o apl-IndexExpr.o apl-IndexIterator.o apl-InputFile.o
... apl-IntCell.o apl-IO_Files.o apl-LApack.o apl-LibPaths.o
... apl-LineInput.o apl-Logging.o apl-LvalCell.o apl-Malloc_hooks.o
... apl-Nabla.o apl-Macro.o apl-Missing_Libraries.o
... apl-NamedObject.o apl-NativeFunction.o apl-NumericCell.o
... apl-Output.o apl-Parallel.o apl-Parser.o apl-Performance.o
... apl-PointerCell.o apl-Prefix.o apl-Plot_line_properties.o
... apl-Plot_data.o apl-Plot_window_properties.o
```

```
1035... apl-PrimitiveFunction.o apl-PrintBuffer.o apl-QuadFunction.o
... apl-ProcessorID.o apl-Quad_CR.o apl-Quad_DLX.o apl-Quad_FFT.o
... apl-Quad_FIO.o apl-Quad_FX.o apl-Quad_GTK.o apl-Quad_JSON.o
... apl-Quad_MAP.o apl-Quad_PLOT.o apl-Quad_PNG.o apl-Quad_RE.o
... apl-Quad_RL.o apl-Quad_RVAL.o apl-Quad_SQL.o apl-Quad_SVx.o
... apl-Quad_TF.o apl-Quad_WA.o apl-Quad_XML.o apl-RealCell.o
... apl-sbrk.o apl-Shape.o apl-ScalarFunction.o apl-Security.o
... apl-StateIndicator.o apl-Svar_DB.o apl-Svar_record.o
... apl-Symbol.o apl-SymbolTable.o apl-SystemVariable.o
... apl-TabExpansion.o apl-Thread_context.o apl-Token.o
... apl-Tokenizer.o apl-UCS_string.o apl-UCS_string_vector.o
... apl-UserFunction.o apl-UserFunction_header.o
... apl-UserPreferences.o apl-UTF8_string.o apl-Value.o
... apl-ValueHistory.o apl-Workspace.o apl-static_Objects.o
... sql/apl-SqliteArgListBuilder.o sql/apl-SqliteConnection.o
... sql/apl-SqliteResultValue.o sql/apl-SqliteProvider.o
... sql/apl-Connection.o -Wl,-bind_at_load -L/usr/local/lib
... /usr/local/lib/libsqlite3.dylib -lpng -lcairo -ldl -lm
... -lncurses -lcurses -lpthread -lz
1036 Making all in support-files
1037 Making all in Bill_Daly_Ubuntu
1038 make[3]: Nothing to be done for `all'.
1039 Making all in Dyalog-Keyboard
1040 make[3]: Nothing to be done for `all'.
1041 Making all in Dirk
1042 make[3]: Nothing to be done for `all'.
1043 Making all in Juergen-Mint-19
1044 make[3]: Nothing to be done for `all'.
1045 Making all in old-Keyboard
1046 make[3]: Nothing to be done for `all'.
1047 Making all in OS-X-Keyboard
1048 make[3]: Nothing to be done for `all'.
1049 Making all in Unicomp-Keyboard
1050 make[3]: Nothing to be done for `all'.
1051 Making all in WASD-Keyboard
1052 make[3]: Nothing to be done for `all'.
1053 Making all in 105-key-International-Keyboard
1054 make[3]: Nothing to be done for `all'.
1055 make[3]: Nothing to be done for `all-am'.
1056 Making all in tools
1057 depbase=`echo APL_keyboard.o | sed
```

```
1057... 's|[^/]*$|.deps/&;s|\.$||'`;\  
1058      g++ -DHAVE_CONFIG_H -I. -I..      -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT APL_keyboard.o  
... -MD -MP -MF $depbase.Tpo -c -o APL_keyboard.o APL_keyboard.cc  
... &&\n  
1059      mv -f $depbase.Tpo $depbase.Po  
1060 /bin/sh ../libtool --tag=CXX --mode=link g++ -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o APL_keyboard  
... APL_keyboard.o -lpng -lcairo -ldl -lm -lncurses -lcurses  
... -lpthread -lz  
1061 libtool: link: g++ -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o APL_keyboard  
... APL_keyboard.o -Wl,-bind_at_load -lpng -lcairo -ldl -lm  
... -lncurses -lcurses -lpthread -lz  
1062 depbase=`echo APL_keyboard_learn.o | sed  
... 's|[^/]*$|.deps/&;s|\.$||'`;\  
1063      g++ -DHAVE_CONFIG_H -I. -I..      -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT  
... APL_keyboard_learn.o -MD -MP -MF $depbase.Tpo -c -o  
... APL_keyboard_learn.o APL_keyboard_learn.cc &&\n  
1064      mv -f $depbase.Tpo $depbase.Po  
1065 /bin/sh ../libtool --tag=CXX --mode=link g++ -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o  
... APL_keyboard_learn APL_keyboard_learn.o -lpng -lcairo -ldl -lm  
... -lncurses -lcurses -lpthread -lz  
1066 libtool: link: g++ -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o  
... APL_keyboard_learn APL_keyboard_learn.o -Wl,-bind_at_load  
... -lpng -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz  
1067 depbase=`echo APL_keyboard_show.o | sed  
... 's|[^/]*$|.deps/&;s|\.$||'`;\  
1068      g++ -DHAVE_CONFIG_H -I. -I..      -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT  
... APL_keyboard_show.o -MD -MP -MF $depbase.Tpo -c -o  
... APL_keyboard_show.o APL_keyboard_show.cc &&\n  
1069      mv -f $depbase.Tpo $depbase.Po  
1070 /bin/sh ../libtool --tag=CXX --mode=link g++ -g -O2 -I  
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o  
... APL_keyboard_show APL_keyboard_show.o -lpng -lcairo -ldl -lm  
... -lncurses -lcurses -lpthread -lz  
1071 libtool: link: g++ -g -O2 -I
```

```
1071... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o
... APL_keyboard_show APL_keyboard_show.o -Wl,-bind_at_load -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
1072 depbase=`echo apl2html.o | sed 's|[^/]*$|.deps/&;s|\.$||'`; \
1073     g++ -DHAVE_CONFIG_H -I. -I.. -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT apl2html.o -MD
... -MP -MF $depbase.Tpo -c -o apl2html.o apl2html.cc && \
1074     mv -f $depbase.Tpo $depbase.Po
1075 /bin/sh ../libtool --tag=CXX --mode=link g++ -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o apl2html
... apl2html.o -lpng -lcairo -ldl -lm -lncurses -lcurses -lpthread
... -lz
1076 libtool: link: g++ -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o apl2html
... apl2html.o -Wl,-bind_at_load -lpng -lcairo -ldl -lm -lncurses
... -lcurses -lpthread -lz
1077 depbase=`echo phrase_gen.o | sed
... 's|[^/]*$|.deps/&;s|\.$||'`; \
1078     g++ -DHAVE_CONFIG_H -I. -I.. -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT phrase_gen.o
... -MD -MP -MF $depbase.Tpo -c -o phrase_gen.o phrase_gen.cc && \
1079     mv -f $depbase.Tpo $depbase.Po
1080 /bin/sh ../libtool --tag=CXX --mode=link g++ -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o phrase_gen
... phrase_gen.o -lpng -lcairo -ldl -lm -lncurses -lcurses
... -lpthread -lz
1081 libtool: link: g++ -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o phrase_gen
... phrase_gen.o -Wl,-bind_at_load -lpng -lcairo -ldl -lm
... -lncurses -lcurses -lpthread -lz
1082 depbase=`echo sockconst.o | sed 's|[^/]*$|.deps/&;s|\.$||'`; \
1083     gcc -DHAVE_CONFIG_H -I. -I.. -g -O2 -MT sockconst.o -MD
... -MP -MF $depbase.Tpo -c -o sockconst.o sockconst.c && \
1084     mv -f $depbase.Tpo $depbase.Po
1085 /bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o
... sockconst sockconst.o -lpng -lcairo -ldl -lm -lncurses
... -lcurses -lpthread -lz
1086 libtool: link: gcc -g -O2 -o sockconst sockconst.o -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
1087 depbase=`echo TLV_server.o | sed
... 's|[^/]*$|.deps/&;s|\.$||'`; \
```

```
1088 gcc -DHAVE_CONFIG_H -I. -I.. -g -O2 -MT TLV_server.o
... -MD -MP -MF $depbasedir.Tpo -c -o TLV_server.o TLV_server.c &&\
1089 mv -f $depbasedir.Tpo $depbasedir.Po
1090 /bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o
... TLV_server TLV_server.o -lpng -lcairo -ldl -lm -lncurses
... -lcurses -lpthread -lz
1091 libtool: link: gcc -g -O2 -o TLV_server TLV_server.o -lpng
... -lcairo -ldl -lm -lncurses -lcurses -lpthread -lz
1092 depbase=`echo ncurses_emul.o | sed
... 's|[^/]*$|.deps/&|;s|\.$||'`; \
1093 g++ -DHAVE_CONFIG_H -I. -I.. -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -MT ncurses_emul.o
... -MD -MP -MF $depbasedir.Tpo -c -o ncurses_emul.o ncurses_emul.cc
... &&\
1094 mv -f $depbasedir.Tpo $depbasedir.Po
1095 /bin/sh ../libtool --tag=CXX --mode=link g++ -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o ncurses_emul
... ncurses_emul.o -lpng -lcairo -ldl -lm -lncurses -lcurses
... -lpthread -lz
1096 libtool: link: g++ -g -O2 -I
... /Volumes/Data/GNUAPL-on-Mac-WS/GNUapl/trunk -o ncurses_emul
... ncurses_emul.o -Wl,-bind_at_load -lpng -lcairo -ldl -lm
... -lncurses -lcurses -lpthread -lz
1097 Making all in websocket
1098 Making all in client
1099 make[3]: Nothing to be done for `all'.
1100 Making all in server
1101 make[3]: Nothing to be done for `all'.
1102 make[3]: Nothing to be done for `all-am'.
1103 make[2]: Nothing to be done for `all-am'.
1104 Gandalf:trunk pteeson$
1105
```